



A

add/drop mux/demux modules

description [1-2](#)

interfaces [2-7, 2-8, 2-9](#)

See also mux/demux modules

aggregate shelf Ethernet interfaces. See ASE interfaces

alarm threshold

rates (table) [4-10](#)

alarm thresholds

configuring [4-9](#)

description [4-8](#)

displaying configuration [4-11](#)

MIBs [9-12](#)

ALS

laser safety control and [4-14](#)

APS

configuring dual shelf nodes [6-9 to 6-11](#)

configuring line card protection [5-6 to 5-10](#)

configuring splitter protection [5-2 to 5-6](#)

lockouts [5-19 to 5-25](#)

MIBs [9-13](#)

switchovers [5-19 to 5-25](#)

aps clear command [5-24](#)

aps direction command [5-14](#)

aps disable command [5-4, 5-9, 5-14, 6-10](#)

aps enable command [5-4, 5-9, 5-14, 6-10](#)

aps far-end command [6-10](#)

aps lockout command [5-22](#)

APS lockouts. See lockouts

aps protection command [5-4, 5-9, 6-10](#)

aps revertive command [5-9](#)

aps switch command [5-21, 5-22](#)

APS switchovers. See switchovers

aps timer oscp holddown command [5-14](#)

aps timer oscp max-interval command [5-14](#)

aps timer search-for-up command [5-4](#)

aps timer switchover min-interval command [5-4](#)

aps timer wait-to-restore command [5-9](#)

aps trigger command [4-9](#)

aps working command [5-4, 5-9, 5-14, 6-10](#)

aps y-cable command [5-9, 6-10](#)

ASE interfaces

not supported (note) [2-9](#)

associate group command [5-4, 5-9, 5-14, 6-9](#)

associate interface command [5-4](#)

autoboot

configuring [3-14](#)

displaying configuration [3-14](#)

See also booting

automatic laser shutdown. See ALS

Automatic Protection Switching. See APS

automatic synchronization

causes (table) [3-16](#)

configuring [3-16](#)

auto-sync running-config command [3-16](#)

auto-sync startup-config command [3-16](#)

auxiliary ports

interface naming convention [2-9](#)

modem support [3-2](#)

B

bands

description [1-2](#)

bidirectional path switching
 configuring [5-14](#)
 description [5-13](#)
 displaying configuration [5-18](#)
 example (figure) [5-15](#)
 figure [5-13](#)

boot system command [3-14](#)

C

CDP

clearing information [9-5](#)
 configuring [9-3 to 9-7](#)
 description [9-3](#)
 displaying configuration [9-4](#)
 displaying information [9-4](#)

cdp advertise-v2 command [9-3](#)

cdp holdtime command [9-3](#)

cdp run command [9-3](#)

cdp timer command [9-3](#)

channel bands. See bands

channels
 description [1-2](#)
 OSC [1-5](#)
 See also data channels

Cisco Discovery Protocol. See CDP

Cisco ONS 15540
 configuration overview [2-10](#)
 starting up [3-2](#)
 See also hardware; shelf; software

CiscoView. See Embedded CiscoView

CiscoWorks2000
 support [1-5](#)

clear cdp counters command [9-5](#)

clear cdp table command [9-5](#)

CLI
 description [2-1](#)
 help [2-3](#)

client equipment
 monitoring [9-17](#)

client protection
 configuring [5-7, 5-8](#)
 description [5-7](#)
 See also line card protection; y-cable protection

client signals
 transparent interfaces and [2-6](#)
 transponder support [1-3](#)

clock rate command [4-3](#)

clock rates
 configuring [4-2](#)
 displaying configuration [4-5](#)
 laser shutdown and (note) [4-5](#)

command-line interface. See CLI

command modes
 description [2-1](#)
 table [2-2](#)

commands
 abbreviating [2-3](#)
 listing [2-3](#)
 syntax in documentation [xiv](#)

compliance [1-4](#)

components
 description [1-2 to 1-4](#)

config-register command [3-14](#)

configuration register
 changing value [3-14](#)

configurations
 displaying [3-5](#)
 overview of tasks [2-10](#)
 synchronizing [3-15 to 3-16](#)

console ports
 configuring modem support [3-2](#)
 using [3-2](#)
 See also NME

conventions
 document [xv](#)
 naming interfaces [2-4 to 2-9](#)

CPUs. See processor cards

cross connections

description 4-20

displaying 4-20

D

data channels

OSC and 1-5, 9-1

transponder module support 1-3

description command 4-9

diagnostic tests. See online diagnostics

digital video. See DV

documentation

conventions xv

related xiv

dual shelf nodes

configuring 6-1 to 6-11

description 6-1

duplex command 3-4

DV

support on transponder modules 4-4

E

Embedded CiscoView

accessing 9-21

description 9-18

download URL 9-18

installing 9-18 to 9-22

enable password command 3-4

enable passwords

description 3-3

enable secret command 3-4

enable secret passwords

description 3-3

encapsulation. See protocol encapsulation

encapsulation command 4-3

Enterprise Systems Connection. See ESCON

ESCON

configuring protocol encapsulation (table) 4-3

configuring protocol monitoring 4-6

network topologies and (note) 8-1

Ethernet management ports. See NME

F

Fast Ethernet

configuring protocol encapsulation (table) 4-3

fastethernet 0 interfaces

configuring 3-3 to 3-5

configuring IP addresses 3-4

description 2-9

IP on OSC 9-9

See also NME

fastethernet-sby 0 interfaces

description 2-9

See also NME

FDDI

configuring protocol encapsulation (table) 4-3

Fiber Connection. See FICON

Fibre Channel

configuring protocol encapsulation (table) 4-3

configuring protocol monitoring 4-6

FICON

configuring protocol encapsulation (table) 4-3

configuring protocol monitoring 4-6

filterband interfaces

description 2-8

filtergroup interfaces

description 2-8

filter interfaces

description 2-7

forward laser control

configuring 4-15

description 4-12

displaying configuration 4-16

figure 4-12
 OFC and (caution) 4-15

G

Gigabit Ethernet

configuring protocol encapsulation (table) 4-3
 configuring protocol monitoring 4-6

H

hardware

components 1-2 to 1-4
 features 1-1
 OSC guidelines 9-2
 shelf overview 1-1

Hello hold-down timer

configuring 9-7

Hello inactivity factor

configuring 9-8

Hello interval timer

configuring 9-7

help

CLI 2-3

hostname command 3-6

host names

configuring 3-6

hubbed ring topologies

configuring line card protection 8-20 to 8-36
 configuring splitter protection 8-3 to 8-19
 description 8-2
 example (figure) 8-2

line card protection model (figure) 2-6

naming conventions 2-4 to 2-9

splitter protection model (figure) 2-5

See also specific types of interfaces (for example, filter interfaces)

interface transparent command 4-3

interface wave command 4-15, 4-16, 9-9

interface wavepatch command 5-11

interface wdm command 9-15

IP

configuring on OSC interfaces 9-9 to 9-11

ip address command 3-4, 9-9

IP addresses

configuring on NME 3-4

OSC wave interfaces 9-9

ip route command 9-10

ip unnumbered command 9-10

L

laser control. See forward laser control; laser safety control

laser control forward enable command 4-15

laser control safety enable command 4-16

laser safety control

configuring 4-16

description 4-14

displaying configuration 4-17

figure 4-14

line card protection and 4-16

OFC and (caution) 4-16

splitter protection and (caution) 4-14, 5-3

laser shutdown

configuring 4-15 to 4-17

description 4-12 to 4-14

line card motherboards

configuring for line card protection 5-11

description 1-2

displaying cross connections (example) 4-21

interface loopback command 9-9

interfaces

configuration overview 4-1

- splitter protection and [5-2](#)
 - wavepatch interfaces [2-7](#)
 - line card protection
 - configuring dual shelf topologies [6-1 to 6-11](#)
 - configuring hubbed ring topologies [8-20 to 8-36](#)
 - configuring meshed ring topologies [8-60 to 8-74](#)
 - configuring point-to-point topologies [7-5 to 7-8](#)
 - configuring splitter protected line card motherboards [5-11](#)
 - configuring y-cable protection [5-8](#)
 - considerations [5-7](#)
 - description [5-6](#)
 - displaying cross connections (example) [4-21](#)
 - example (figure) [5-7](#)
 - interface model (figure) [2-6](#)
 - lockouts [5-19 to 5-25](#)
 - switchovers [5-19 to 5-25](#)
 - See also y-cable protection
 - line card redundancy controllers. See LRCs
 - line vty command [3-4](#)
 - lockouts
 - clearing [5-24](#)
 - description [5-19](#)
 - displaying status [5-23, 5-25](#)
 - requesting [5-22](#)
 - logical mesh topologies. See meshed ring topologies
 - LRCs
 - description [1-4](#)
-
- M**
- maintenance-mode command [3-17](#)
 - management ports. See NME
 - management systems. See network management systems
 - meshed ring topologies
 - configuring line card protection [8-60 to 8-74](#)
 - configuring line card protection with unprotected channels [8-74 to 8-83](#)
 - configuring splitter protection [8-37 to 8-51](#)
 - configuring splitter protection with unprotected channels [8-52 to 8-59](#)
 - description [8-3](#)
 - example (figure) [8-3](#)
 - MIBs
 - enabling [9-13 to 9-14](#)
 - processor support [3-1](#)
 - supported [9-12](#)
 - modem
 - support [3-2](#)
 - monitor enable command [4-7](#)
 - monitoring. See network monitoring; protocol monitoring
 - mux/demux cabling
 - dual shelf nodes [6-2 to 6-7](#)
 - hubbed ring topologies with line card protection, example [8-21, 8-26, 8-29, 8-32, 8-35](#)
 - hubbed ring topologies with splitter protection, example [8-5, 8-9, 8-12, 8-15, 8-18](#)
 - meshed ring topologies with line card protection, example [8-61, 8-65, 8-68, 8-72](#)
 - meshed ring topologies with splitter protection, example [8-39, 8-43, 8-46, 8-49](#)
 - meshed ring topologies with unprotected channels, line card protection, example [8-76, 8-80](#)
 - meshed ring topologies with unprotected channels, splitter protection, example [8-54, 8-57](#)
 - point-to-point topologies with line card protection, 32 channels, example [6-4](#)
 - point-to-point topologies without protection, example [7-10](#)
 - mux/demux modules
 - configuring for line card protection [5-8](#)
 - description [1-4](#)
 - interfaces [2-7, 2-8](#)
 - See also add/drop mux/demux modules; terminal mux/demux modules
 - mux/demux motherboards
 - description [1-2](#)

N

network management Ethernet. See NME

network management systems

supported 1-5

See also Embedded CiscoView

network monitoring

CDP 9-3 to 9-5

Embedded CiscoView 9-18 to 9-22

OSCP 9-7 to 9-9

transparent interfaces 9-17

without OSC 9-15 to 9-17

Network Time Protocol. See NTP

network topologies

adding transparent interfaces 9-17

adding wdm interfaces 9-5

MIBs 9-13, 9-14

types 1-6

See also hubbed ring topologies; meshed ring topologies; point-to-point topologies

NME

configuring interfaces 3-3

description 2-9

displaying configuration 3-5

using 3-2

See also fastethernet 0 interfaces

notification-throttle timer command 4-9

NTP

configuring 3-7

description 3-6

displaying configuration 3-8

ntp server command 3-7

ntp update-calendar command 3-7

O

OADM. See add/drop mux/demux modules

OFC

configuring with encapsulation command 4-3

description 4-13

figure 4-13

forward laser control and (caution) 4-15

laser safety control and (caution) 4-16

online diagnostics

description 1-6

open fiber control. See OFC

optical add/drop mux/demux modules. See add/drop mux/demux modules

optical budgets. See optical power budgets

optical connections. See cross connections

optical mux/demux motherboards. See mux/demux motherboards

optical power budgets

system specifications 1-4

optical supervisory channel. See OSC

Optical Supervisory Channel Protocol. See OSCP

optical terminal mux/demux modules. See terminal mux/demux modules

OSC

description 1-5, 9-1 to 9-2

hardware guidelines 9-2

OSCP 9-7 to 9-9

signal path (figure) 9-2

oscfilter interfaces

configuring patch connections 4-18

description 2-9

OSC interfaces

configuring CDP 9-3 to 9-5

configuring IP 9-9 to 9-11

description 2-9

patch connections 4-18

OSCP

configuring 9-7 to 9-8

description 9-2

displaying configuration 9-8

displaying neighbors 9-8

MIBs 9-13

OSC Protocol. See OSCP

oscp timer hello holddown command [9-7](#)

oscp timer hello interval command [9-7](#)

oscp timer inactivity-factor command [9-8](#)

P

passwords

description [3-3](#)

patch command [4-18](#)

patch connections

configuring [4-2, 4-18 to 4-19](#)

description [4-17](#)

displaying configuration [4-19](#)

types (table) [4-17](#)

path lockouts. See lockouts

path switching

configuring [5-14 to 5-19](#)

description [5-12 to 5-14](#)

example (figure) [5-12](#)

y-cable protection and [5-16 to 5-18](#)

path switchovers. See switchovers

point-to-point topologies

configuring line card protection [7-5 to 7-8](#)

configuring splitter protection [7-3](#)

configuring without protection [7-9 to 7-11](#)

description [7-1](#)

example without protection (figure) [7-2](#)

example with protection (figure) [7-2](#)

power budgets. See optical power budgets

processor cards

autoboot [3-14](#)

configuring [3-12 to 3-20](#)

description [1-4, 3-1](#)

hardware state transitions [3-9](#)

interfaces [2-9](#)

redundant [3-13](#)

reloading [3-20](#)

slot assignments [1-2](#)

software state transitions [3-10](#)

starting up [3-2](#)

processor redundancy. See redundancy

processors. See processor cards

processor switchovers

forcing [3-12 to 3-13](#)

protection

description [5-1](#)

types [5-2 to 5-10](#)

protection switching. See path switching

protocol encapsulation

configuring [4-2](#)

displaying configuration [4-5](#)

types supported [1-3](#)

protocol monitoring

configuring [4-7](#)

description [4-6](#)

displaying configuration [4-7](#)

Q

quick laser shutdown. See forward laser control; laser safety control

R

redundancy

configuring [3-12 to 3-20](#)

description [3-8 to 3-11](#)

displaying alarm status (note) [3-8](#)

displaying configuration [3-17](#)

forcing switchovers [3-12 to 3-13](#)

MIBS [9-14](#)

processor hardware state transitions [3-9](#)

processor software state transitions [3-10](#)

synchronizing configurations [3-15](#)

redundancy command [3-16, 5-4](#)

redundancy manual-sync command [3-15](#)

redundancy reload peer command [3-20](#)

redundancy reload shelf command [3-20](#)
 redundancy switch-activity command [3-12](#)
 reset command [3-13](#)
 reshape, retime, retransmit functions. See 3R functions
 ring topologies
 description [8-1 to 8-3](#)
 See also hubbed ring topologies; meshed ring topologies
 router bgp command [9-10](#)
 router eigrp command [9-10](#)
 router ospf command [9-10](#)

S

SDH

configuring protocol encapsulation (table) [4-3](#)
 configuring protocol monitoring [4-6](#)

shelf

configuration examples
 hubbed ring topologies with splitter protection [8-8, 8-14](#)
 point-to-point topologies with line card protection, 32 channels [6-3, 6-6](#)
 point-to-point topologies without protection [7-9](#)
 configuration overview [2-10](#)
 description [1-1](#)
 layout (figure) [1-2](#)
 starting up [3-2](#)

show aps command [5-5, 5-10](#)
 show bootvar command [3-14](#)
 show cdp command [9-4](#)
 show cdp entry command [9-4](#)
 show cdp interface command [9-4](#)
 show cdp neighbor command [9-4](#)
 show cdp traffic command [9-4](#)
 show ciscoview package command [9-21](#)
 show ciscoview version command [9-21](#)
 show connect command [4-20](#)
 show hardware command [3-4](#)
 show interfaces transparent command [4-5](#)

show ntp status command [3-8](#)
 show oscp info command [9-8](#)
 show oscp neighbor command [9-8](#)
 show patch command [4-19](#)
 show redundancy capability command [3-17](#)
 show redundancy command [3-17](#)
 show redundancy running-config-file command [3-17](#)
 show threshold-list command [4-11](#)
 show topology command [9-6, 9-17](#)
 show topology neighbor command [9-16](#)
 show version command [3-14](#)
 shutdown command [4-5, 5-11](#)

Simple Network Management Protocol. See SNMP
 SNMP

configuring [9-11](#)
 configuring alarm thresholds (table) [4-9](#)
 processor support [3-1](#)

snmp-server enable traps aps command [9-13](#)
 snmp-server enable traps oscp command [9-13](#)
 snmp-server enable traps patch command [9-13](#)
 snmp-server enable traps rf command [9-14](#)
 snmp-server enable traps threshold min-severity command [9-12](#)
 snmp-server enable traps topology command [9-14](#)
 software

features [1-4 to 1-6](#)

SONET

configuring protocol encapsulation (table) [4-3](#)
 configuring protocol monitoring [4-6](#)

SONET APS. See APS

speed command [3-4](#)

splitter protection

configuring [5-3](#)
 configuring hubbed ring topologies [8-3 to 8-19](#)
 configuring meshed ring topologies [8-37 to 8-51](#)
 configuring meshed ring topologies with unprotected channels [8-52 to 8-59](#)
 configuring point-to-point topologies [7-3](#)
 considerations [5-2](#)

- description [5-2](#)
- displaying configuration [5-5](#)
- displaying cross connections (example) [4-21](#)
- example (figure) [5-2](#)
- figure [2-5](#)
- interface model (figure) [2-5](#)
- lockouts [5-19 to 5-25](#)
- switchovers [5-19 to 5-25](#)

SRCs

- description [1-4](#)

standards compliance. See [compliance](#)

switchcard redundancy controllers. See [SRCs](#)

switchover command [3-13](#)

switchovers

- clearing [5-24](#)
- description [5-19](#)
- displaying status [5-21, 5-25](#)
- requesting [5-21](#)

synchronizing

- configurations [3-15 to 3-16](#)

Synchronous Digital Hierarchy. See [SDH](#)

T

telnet command [9-11](#)

terminal mux/demux modules

- description [1-3](#)
- interfaces [2-8, 2-9](#)
- subcard position numbering [2-8, 2-9](#)

See also [mux/demux modules](#)

threshold command [4-9](#)

threshold-group command [4-9](#)

threshold-list command [4-9](#)

thresholds. See [alarm thresholds](#)

thru interfaces

- configuring patch connections [4-18](#)
- description [2-8](#)

topologies. See [network topologies](#)

topology hold-time command [9-6](#)

topology neighbor agent ip-address command [6-8, 9-15, 9-17](#)

topology neighbor cdp command [9-6](#)

topology neighbor command [6-8, 9-15, 9-17](#)

topology neighbor disable command [9-6](#)

transparent interfaces

- adding to network topology [9-17](#)
- configuration overview [4-1](#)
- configuring alarm thresholds [4-8 to 4-12](#)
- configuring clock rates [4-2](#)
- configuring protocol encapsulation [4-2](#)
- configuring protocol monitoring [4-6](#)
- description [2-6](#)
- displaying network topology information [9-17](#)

transponder modules

- description [1-2, 1-3](#)
- interfaces [2-6, 2-7](#)
- shutting down lasers [4-12 to 4-17](#)
- splitter protection and [5-2](#)
- y-cable protection and [5-7](#)

troubleshooting

- cross connections [4-20](#)
- online diagnostics [1-6](#)
- shelf misconfigurations [4-19](#)

U

unidirectional path switching

- configuring [5-14](#)
- description [5-13](#)
- displaying configuration [5-18](#)
- example (figure) [5-13](#)

unprotected channels

- configuring in meshed ring topologies [8-52 to 8-59, 8-74 to 8-83](#)
- configuring in point-to-point topologies [7-9 to 7-11](#)

V

value command [4-9](#)

W

wave interfaces

- configuration overview [4-1](#)
- configuring alarm thresholds [4-8 to 4-12](#)
- configuring forward laser control [4-15](#)
- configuring laser safety control [4-16](#)
- configuring patch connections [4-18](#)
- description [2-7](#)
- protocol monitoring [4-6](#)

wavepatch interfaces

- description [2-7](#)

wdm interfaces

- adding manually to network topologies,
example [9-15 to 9-17](#)
 - configuring CDP [9-5](#)
 - configuring patch connections [4-18](#)
 - description [2-8](#)
 - displaying CDP information [9-6](#)
-

Y

y-cable protection

- configuring [5-9](#)
 - displaying configuration [5-10](#)
 - path switching and [5-16 to 5-18](#)
- See also line card protection