



Numerics

2.5-Gbps line card motherboards

- description [1-11](#)
- optical link loss [4-4](#)
- shelf configuration rules [3-12](#)

3R functions

- support for [1-4](#)
- transponders and [1-3](#)

4-channel mux/demux modules

- band pairings without splitter protection (table) [3-4](#)
- cabling rules [3-9](#)
- conflicting bands (table) [3-1](#)
- line card protection, example (figure) [3-4](#)
- optical link loss for data channels (table) [4-4](#)
- optical link loss for OSC (table) [4-5](#)
- shelf configuration rules without splitter protection [3-3](#)
- shelf configuration rules with splitter protection [3-2](#)
- transponder module placement with [3-5 to 3-7](#)
- See also add/drop mux/demux modules

8-channel mux/demux modules

- cabling rules [3-9](#)
- conflicting bands (table) [3-1](#)
- optical link loss for data channels (table) [4-4](#)
- optical link loss for OSC (table) [4-5](#)
- shelf configuration rules without splitter protection [3-4](#)
- shelf configuration rules with splitter protection [3-2](#)
- splitter protection example (figure) [3-3](#)
- transponder placement with [3-8 to 3-9](#)
- See also add/drop mux/demux modules

16-channel mux/demux modules

- cabling rules [3-12](#)
- optical link loss for data channels (table) [4-5](#)

- optical link loss for OSC (table) [4-5](#)
- shelf configuration rules [3-10](#)
- transponder module placement with [3-10 to 3-12](#)
- See also terminal mux/demux modules

A

add/drop mux/demux modules

- cascaded (figure) [1-14](#)
- cascaded in protected ring configurations (figure) [1-15](#)
- combining [1-13](#)
- description [1-12](#)
- logical view (figure) [1-13](#)
- physical layout [1-12](#)
- protected ring configurations (figure) [1-14](#)
- ring configurations [1-14](#)
- transponder placement with [3-5 to 3-8](#)
- See also 4-channel mux/demux modules; 8-channel mux/demux modules; mux/demux cabling; mux/demux modules

APS

- support for [1-2](#)

architecture

- description [1-3](#)
- figure [1-3](#)

ATM

- client equipment attenuation [A-4](#)
- client interface support [1-5](#)

attenuation

- ESCON and [A-4](#)
- line card motherboards [4-4](#)
- minimum for data channels [4-3](#)
- mux/demux modules [4-4](#)

Automatic Protection Switching. See APS

B

band allocation. See channel plans

bands

- add/drop mux/demux modules and [1-12](#)
- conflicting [3-1](#)
- mux/demux modules and [1-12](#)
- mux/demux module support (table) [1-12](#)
- terminal mux/demux modules and [1-13](#)

bidirectional path switching

- description [2-12](#)

bus topologies

- description [2-8](#)
 - figure [2-8](#)
-

C

cabling. See mux/demux cabling

channel plans

- hubbed ring topologies, example [5-11](#)
- meshed ring topologies, example [5-34](#)
- meshed ring topologies with unprotected channels, example [5-53](#)

channels. See bands; data channels; OSC

chassis

- description [1-1](#)
- figure [1-2](#)
- optical backplane [2-3](#)

client protection

- description [2-6](#)
- implementation considerations [2-6](#)
- scheme (figure) [2-6](#)

client side interfaces

- encapsulation types [1-4](#)
- OFC [1-7](#)

components

- description [1-3 to 1-16](#)

Coupling Facility links

- client interface support [1-6](#)

- description [A-3](#)

CPUs. See processor cards

D

data channels

- maximum number supported [1-2](#)
- optical link loss through 4-channel mux/demux modules [4-4](#)
- optical link loss through 8-channel mux/demux modules [4-4](#)
- optical link loss through 16-channel mux/demux modules [4-5](#)
- receiver sensitivity (table) [4-2](#)
- transmit power (table) [4-2](#)

dBs

- about [4-1](#)
- dBm [4-2](#)

decibels. See dBs

dense wavelength division multiplexing. See DWDM

documentation

- related [viii](#)

DS3

- client interface support [1-6](#)

dual shelf nodes

- configuring [5-8 to 5-10](#)

DWDM

- interfaces [1-2](#)
-

E

east/west motherboards. See line card motherboards

encapsulations [1-5](#)

Enterprise Systems Connection. See ESCON

ESCON

- client equipment attenuation [A-4](#)
- client interface support [1-5](#)
- client side attenuation [A-4](#)
- configuring protocol monitoring [1-9](#)

data rate as function of distance (figure) [A-3](#)
 extended range transponder modules
 description [1-7](#)
 extended remote copy. See XRC

F

Fast Ethernet

client interface support [1-4](#)

FDDI

client equipment attenuation [A-4](#)

client interface support [1-5](#)

fiber

testing requirements [4-5](#)

Fiber Connection. See FICON

fiber failure

protection against [2-1](#)

Fibre Channel

autonegotiation support [1-7, 1-9, 1-10](#)

client interface support [1-5](#)

configuring protocol monitoring [1-9](#)

FICON

client equipment attenuation [A-4](#)

client interface support [1-5](#)

configuring protocol monitoring [1-9](#)

description [A-3](#)

G

GDPS

description [A-4](#)

environment (figure) [A-1](#)

Gigabit Ethernet

client interface support [1-4](#)

configuring protocol monitoring [1-9](#)

H

hubbed ring topologies

configuring line card protection [5-22 to 5-33](#)

configuring splitter protection [5-11 to 5-22](#)

description [2-9](#)

example (figure) [2-9](#)

optical power budget with line card protection,
 example [5-23](#)

optical power budget with splitter protection,
 example [5-12](#)

I

IBM protocols

attenuation requirements [A-4](#)

optical power budget [A-4](#)

supported types [A-2 to A-4](#)

interfaces

processor [1-15](#)

transponder [1-4](#)

types [1-4](#)

ISC compatibility

client equipment attenuation [A-4](#)

ITU-T G.692

laser grid [1-2](#)

L

linear topologies. See bus topologies; point-to-point topologies

line card motherboards

description [1-11](#)

optical link loss (table) [4-4](#)

per shelf configuration rules [3-12, 3-13](#)

line card protection

client based [2-6](#)

configuring hubbed ring topologies [5-22 to 5-33](#)

configuring meshed ring topologies [5-44 to 5-52](#)

configuring meshed ring topologies with unprotected channels [5-58 to 5-63](#)

configuring point-to-point topologies [5-6 to 5-10](#)

y-cable based [2-4](#)

link loss. See optical link loss

logical mesh topologies. See meshed ring topologies

M

meshed ring topologies

adding unprotected channels [5-52](#)

configuring line card protection [5-44 to 5-52](#)

configuring line card protection with unprotected channels [5-58 to 5-63](#)

configuring splitter protection [5-35 to 5-43](#)

configuring splitter protection with unprotected channels [5-53 to 5-58](#)

description [2-10, 5-52](#)

example (figure) [2-10](#)

optical power budgets, examples [5-35, 5-44](#)

MM fiber. See multimode fiber

multimode fiber

other supported client signal encapsulations [1-6](#)

supported IBM storage protocols [1-5](#)

mux/demux cabling

description [3-9](#)

hubbed ring topologies with line card protection, example [5-25, 5-27, 5-29, 5-31, 5-33](#)

hubbed ring topologies with splitter protection, example [5-14, 5-16, 5-18, 5-20, 5-22](#)

meshed ring topologies with line card protection, example [5-46, 5-48, 5-49, 5-52](#)

meshed ring topologies with splitter protection, example [5-37, 5-39, 5-41, 5-43](#)

meshed ring topologies with unprotected channels, line card protection, example [5-61, 5-63](#)

meshed ring topologies with unprotected channels, splitter protection, example [5-56, 5-58](#)

point-to-point topologies with line card protection, 32 channels, example [5-10](#)

point-to-point topologies with line card protection, 16 channels, example [5-8](#)

point-to-point topologies without protection, example [5-4](#)

point-to-point topologies with splitter protection, example [5-6](#)

rules [3-9, 3-12](#)

mux/demux modules

bands supported [1-12](#)

configurations [1-13](#)

mapping to transponder modules (figure) [2-4](#)

meshed ring topologies and [5-34](#)

motherboards [1-11](#)

See also 4-channel mux/demux modules; 8-channel mux/demux modules; 16-channel mux/demux modules; add/drop mux/demux modules; mux/demux cabling; terminal mux/demux modules

N

network management

comparison (table) [1-17](#)

description [1-16](#)

NME

network management Ethernet

See NME

NME

description [1-17](#)

O

OC-1

client interface support [1-6](#)

OC-24

client interface support [1-6](#)

OFC

client signal encapsulation types supported [1-7](#)

open fiber control. See OFC

optical backplane

splitter protection and [2-3](#)

transponder to mux/demux module mapping (figure) [2-4](#)

transponder to mux/demux module mapping (table) [2-3](#)

optical link loss

- 2.5-Gbps line card motherboards [4-4](#)
- calculating [4-2](#)
- data channels [4-4](#)
- hubbed ring topologies with line card protection, example [5-23](#)
- hubbed ring topologies with splitter protection, example [5-12](#)
- meshed ring topologies and [5-34](#)
- meshed ring topologies with line card protection, example [5-44](#)
- meshed ring topologies with unprotected channels, line card protected, example [5-59](#)
- meshed ring topologies with unprotected channels, splitter protected, example [5-54](#)
- meshed ring with splitter protection, example [5-35](#)

OSC [4-5](#)

- point-to-point topologies with line card protection, example [5-7](#)
- point-to-point topologies without protection, example [5-2](#)
- point-to-point topologies with splitter protection, example [5-5](#)

See also optical power budgets

optical mux/demux modules. See mux/demux modules

optical power budgets

- overall [4-2](#)

See also optical link loss

optical power loss. See optical link loss

optical supervisory channel. See OSC

OSC

- description [1-11](#)
- information types [1-11](#)
- optical link loss through mux/demux modules [4-5](#)
- receiver sensitivity (table) [4-2](#)
- transmit power (table) [4-2](#)

P

Peer-to-Peer Remote Copy. See PPRC

point-to-point topologies

- configuring line card protection [5-6 to 5-10](#)
- configuring splitter protection [5-4 to 5-6](#)
- configuring without protection [5-2 to 5-4](#)
- description [2-7](#)
- equipment for [5-1](#)
- optical power budgets, example [5-2](#)
- optical power budgets, examples [5-5, 5-7](#)
- protection in [2-7](#)

power supplies

- description [1-1](#)

PPRC

- client interface support [A-2](#)
- description [A-4](#)

processor cards

- description [1-15](#)
- features [1-15](#)

processors. See processor cards

protection

- description [1-2](#)
- levels of [2-1](#)
- ring topologies [2-10](#)
- types [2-1 to 2-6](#)

See also APS; client protection; line card protection; splitter protection; y-cable protection

R

redundancy

- processor cards [1-16](#)

ring topologies

- protection in [2-10 to 2-12](#)
- shelf configuration rules [3-13](#)

See also hubbed ring topologies; meshed ring topologies

S

SANs

- IBM environment [A-1](#)

- SDH
 - client interface support [1-4](#)
 - configuring protocol monitoring [1-9](#)
 - security features
 - overview [1-16](#)
 - SFP optics
 - description [1-7](#)
 - shelf
 - configuration examples
 - hubbed ring topologies with line card protection [5-24](#), [5-26](#), [5-28](#), [5-30](#), [5-32](#)
 - hubbed ring topologies with splitter protection [5-13](#), [5-15](#), [5-17](#), [5-19](#), [5-21](#)
 - meshed ring topologies with line card protection [5-45](#), [5-47](#), [5-49](#), [5-51](#)
 - meshed ring topologies with splitter protection [5-36](#), [5-38](#), [5-40](#), [5-42](#)
 - meshed ring topologies with unprotected channels, line card protected [5-60](#), [5-62](#)
 - meshed ring topologies with unprotected channels, splitter protected [5-55](#), [5-57](#)
 - point-to-point topologies with line card protection, 32 channels [5-9](#)
 - point-to-point topologies with line card protection, 16 channels [5-7](#)
 - point-to-point topologies without protection [5-3](#)
 - point-to-point topologies with splitter protection [5-5](#)
 - configuration rules [3-1 to 3-13](#)
 - shelf configuration rules
 - 4-channel mux/demux modules [3-5 to 3-7](#)
 - 8-channel mux/demux modules [3-8 to 3-9](#)
 - 16-channel mux/demux modules [3-10 to 3-12](#)
 - ring topologies [3-13](#)
 - single-mode fiber
 - other supported client signal encapsulations [1-6](#)
 - supported IBM storage protocols [1-5](#)
 - slot mapping
 - transponder modules to 4-channel mux/demux modules [3-5](#)
 - transponder modules to 8-channel mux/demux modules [3-5](#)
 - transponder modules to 16-channel mux/demux modules [3-10](#)
 - SM fiber. See single-mode fiber
 - SONET
 - client interface support [1-4](#)
 - configuring protocol monitoring [1-9](#)
 - splitter motherboards. See line card motherboards
 - splitter protection
 - 4-channel mux/demux modules and [3-2](#)
 - 8-channel mux/demux modules and [3-2](#)
 - 16-channel mux/demux modules and [3-10](#)
 - configuring hubbed ring topologies [5-11 to 5-22](#)
 - configuring meshed ring topologies [5-35 to 5-43](#)
 - configuring meshed ring topologies with unprotected channels [5-53 to 5-58](#)
 - configuring point-to-point topologies [5-4 to 5-6](#)
 - considerations [2-2](#)
 - description [2-1](#)
 - optical backplane connections for [2-3](#)
 - scheme (figure) [2-2](#)
 - storage area networks
 - See SANs
 - Synchronous Digital Hierarchy. See SDH
 - Sysplex Timer
 - client interface support [1-6](#)
 - IBM storage environment and [A-3](#)
 - system
 - components [1-3 to 1-16](#)
 - functional overview [1-2](#)
 - system management
 - OSC and [1-11](#)
-
- T
 - terminal mux/demux modules
 - description [1-13](#)
 - optical link loss [1-13](#)
 - transponder placement with [3-10 to 3-12](#)
 - See also 16-channel mux/demux modules

theory of operation [1-2](#)

topologies. See bus topologies; hubbed ring topologies; meshed ring topologies; point-to-point topologies

transceivers. See SFP optics

transmitter launch power

- data channels [4-2](#)
- OSC [4-2](#)

transponder modules

- description [1-3](#)
- interfaces [1-4](#)
- line card motherboards [1-11](#)
- line card protection and [3-12, 3-13](#)
- mapping to mux/demux modules (figure) [2-4](#)
- placement for lower channels with 4-channel mux/demux modules [3-5 to 3-6](#)
- placement for upper channels with 4-channel mux/demux modules [3-6 to 3-7](#)
- placement with 8-channel mux/demux modules [3-8 to 3-9](#)
- placement with 16-channel mux/demux modules [3-11 to 3-12](#)

trunk side interfaces

- description [1-4](#)

U

Unidirectional Path Switched Ring. See UPSR

unidirectional path switching

- description [2-10](#)
- example (figure) [2-12](#)
- normal state (figure) [2-11](#)

unprotected channels

- adding [5-52](#)
- configuring in meshed ring topologies [5-53 to 5-63](#)

unprotected topologies. See point-to-point topologies

UPSR

- description [2-10](#)

X

XRC

- client interface support [A-2](#)
- description [A-4](#)

Y

y-cable protection

- considerations [2-5](#)
- description [2-4](#)

