



---

## Numerics

### 2.5-Gbps line card motherboard

description [1-12](#)

optical link loss [4-4](#)

shelf configuration rules [3-6](#)

### 32-channel mux/demux modules

optical link loss for data channels (table) [4-6](#)

optical link loss for OSC (table) [4-6](#)

transponder module placement with [3-5](#)

### 3R functions

support for [1-4](#)

transponders and [1-3](#)

### 4-channel mux/demux modules

cabling rules [3-4](#)

conflicting bands (table) [3-2](#)

line card protection example (figure) [3-4](#)

optical link loss for data channels (table) [4-5](#)

optical link loss for OSC (table) [4-6](#)

shelf configuration rules without splitter protection [3-2](#)

shelf configuration rules with splitter protection [3-2, 3-3](#)

See also add/drop mux/demux modules

### 8-channel mux/demux modules

cabling rules [3-4](#)

conflicting bands (table) [3-2](#)

optical link loss for data channels (table) [4-5](#)

optical link loss for OSC (table) [4-6](#)

shelf configuration rules without splitter protection [3-2](#)

shelf configuration rules with splitter protection [3-2, 3-3](#)

splitter protection example (figure) [3-3](#)

See also add/drop mux/demux modules

### 10-Gbps line card motherboards

protected configurations [5-12](#)

unprotected configurations [5-10](#)

### 10-GE transparent transponder modules

description [1-11](#)

performance monitoring [1-11](#)

---

## A

### add/drop mux/demux modules

cascaded (figure) [1-17](#)

cascaded in protected ring configuration (figure) [1-18](#)

combining [1-16](#)

description [1-15](#)

physical layout [1-15](#)

protected ring configuration (figure) [1-17](#)

ring configurations [1-17](#)

See also 4-channel mux/demux modules; 8-channel mux/demux modules; mux/demux cabling; mux/demux modules

### APS

support for [1-3](#)

### architecture

description [1-3](#)

figure [1-3](#)

### ATM

client equipment attenuation [A-4](#)

client interface support [1-5](#)

### attenuation

ESCON and [A-4](#)

line card motherboards [4-4](#)

minimum for data channels [4-3](#)

mux/demux modules [4-5](#)  
 OADM modules [4-6](#)  
 Automatic Protection Switching. See APS

---

## B

band allocation. See channel plans  
 bands  
   add/drop mux/demux modules and [1-15](#)  
   conflicting [3-2](#)  
   mux/demux modules and [1-14](#)  
   mux/demux module support (table) [1-15](#)  
   terminal mux/demux modules and [1-16](#)  
 bidirectional path switching  
   description [2-12](#)  
 bus topologies  
   description [2-7](#)  
   example (figure) [2-8](#)  
   figure [2-8](#)

---

## C

cabling  
   line card protected configuration example [5-6](#)  
   splitter protected configuration example [5-4](#), [5-5](#), [5-7](#)  
   trunk fiber protected configuration example [5-8](#)  
   unprotected configuration example [5-2](#), [5-3](#)  
 cabling. See mux/demux cabling  
 channel plans  
   hubbed ring topologies, example [5-22](#)  
   meshed ring topologies, example [5-45](#)  
   meshed ring topologies with unprotected channels,  
     example [5-64](#)  
 channels. See bands; data channels; OSC  
 chassis  
   description [1-1](#)  
   figure [1-2](#)

client protection  
   considerations [2-4](#)  
   description [2-4](#)  
   scheme (figure) [2-4](#)  
 client side interfaces  
   encapsulation types [1-4](#)  
   OFC [1-7](#)  
 components  
   description [1-4 to 1-20](#)  
 Coupling Facility links  
   client interface support [1-6](#)  
   description [A-3](#)  
 CPUs. See processor cards  
 cross connect drawer cabling  
   line card protected example [5-7](#)  
   splitter protected example [5-5](#)  
   unprotected example [5-3](#)  
 cross connect drawers  
   cabling rules [3-7](#)  
   description [1-19](#)  
   optical link loss [4-6](#)

---

## D

data channels  
   maximum number supported [1-3](#)  
   optical link loss through 32-channel mux/demux  
     modules [4-6](#)  
   optical link loss through 4-channel mux/demux  
     modules [4-5](#)  
   optical link loss through 8-channel mux/demux  
     modules [4-5](#)  
   optical link loss through OADM modules [4-6](#)  
   receiver sensitivity (table) [4-2](#)  
   transmit power (table) [4-2](#)  
 dBs  
   about [4-1](#)  
   dBm [4-2](#)  
 decibels. See dBs

dense wavelength division multiplexing. See DWDM

direct cabling

line card protected configurations, example [5-6](#)

splitter protected configurations, example [5-4](#)

unprotected configurations, example [5-2](#)

documentation

related [viii](#)

DS3

client interface support [1-7](#)

dual shelf nodes

configuring [5-19 to 5-21](#)

DWDM

interfaces [1-3](#)

---

## E

east/west motherboards. See line card motherboards

encapsulations [1-6](#)

Enterprise Systems Connection. See ESCON

ESCON

client equipment attenuation [A-4](#)

client interface support [1-6](#)

client side attenuation [A-4](#)

configuring protocol monitoring [1-9](#)

data rate as function of distance (figure) [A-3](#)

extended range transponder modules

description [1-7](#)

extended remote copy. See XRC

---

## F

Fast Ethernet

client interface support [1-5](#)

FDDI

client equipment attenuation [A-4](#)

client interface support [1-5](#)

fiber

testing [4-7](#)

Fiber Connection. See FICON

fiber failure

protection against [2-1](#)

Fibre Channel

autonegotiation support [1-7, 1-10](#)

client interface support [1-5](#)

configuring protocol monitoring [1-9](#)

FICON

client equipment attenuation [A-4](#)

client interface support [1-6](#)

configuring protocol monitoring [1-9](#)

description [A-3](#)

---

## G

GDPS

description [A-4](#)

environment (figure) [A-1](#)

Gigabit Ethernet

client interface support [1-5](#)

configuring protocol monitoring [1-9](#)

---

## H

hubbed ring topologies

configuring line card protection [5-33 to 5-44](#)

configuring splitter protection [5-22 to 5-33](#)

description [2-8](#)

example (figure) [2-9](#)

optical power budgets with line card protection,  
example [5-34](#)

optical power budgets with splitter protection,  
example [5-23](#)

---

## I

IBM protocols

attenuation requirements [A-4](#)

Coupling Facility links [A-3](#)

optical power budget [A-4](#)  
 supported types [A-2 to A-4](#)

in-band network channel  
 description [1-20](#)

interfaces  
 processor [1-19](#)  
 transponder [1-4](#)  
 types [1-4](#)

ISC compatibility  
 client equipment attenuation [A-4](#)

ITU-T G.692  
 laser grid [1-3](#)

---

**L**

linear topologies. See bus topologies; point-to-point topologies

line card motherboards  
 description [1-12](#)  
 optical link loss (table) [4-4](#)  
 per shelf configuration rules [3-6](#)

line card protected configuration  
 examples [5-6 to 5-7](#)

line card protection  
 client based [2-4](#)  
 configuring hubbed ring topologies [5-33 to 5-44](#)  
 configuring meshed ring topologies [5-55 to 5-63](#)  
 configuring meshed ring topologies with unprotected channels [5-69 to 5-74](#)  
 configuring point-to-point topologies [5-17 to 5-21](#)  
 y-cable based [2-3](#)

logical mesh topologies. See meshed ring topologies

---

**M**

meshed ring topologies  
 adding unprotected channels [5-63](#)  
 configuring line card protection [5-55 to 5-63](#)

configuring line card protection with unprotected channels [5-69 to 5-74](#)

configuring splitter protection [5-46 to 5-54](#)

configuring splitter protection with unprotected channels [5-64 to 5-69](#)

description [2-9, 5-63](#)

example (figure) [2-10](#)

optical power budgets for line card protected [5-55](#)

optical power budgets for splitter protected [5-46](#)

MM fiber. See multimode fiber.

multimode fiber  
 other supported client signal encapsulations [1-7](#)  
 supported IBM storage protocols [1-6](#)

multiple trunk  
 support [2-12](#)

mux/demux cabling  
 hubbed ring topologies with line card protection, example [5-36, 5-38, 5-40, 5-42, 5-44](#)  
 hubbed ring topologies with splitter protection, example [5-25, 5-27, 5-29, 5-31, 5-33](#)  
 meshed ring topologies with line card protection, example [5-57, 5-59, 5-60, 5-63](#)  
 meshed ring topologies with splitter protection, example [5-48, 5-50, 5-52, 5-54](#)  
 meshed ring topologies with unprotected channels, line card protection, example [5-72, 5-74](#)  
 meshed ring topologies with unprotected channels, splitter protection, example [5-67, 5-69](#)  
 point-to-point topologies with line card protection, 16 channels, example [5-19](#)  
 point-to-point topologies with line card protection, 32 channels, example [5-21](#)  
 point-to-point topologies without protection, example [5-15](#)  
 point-to-point topologies with splitter protection, example [5-17](#)

rules [3-4](#)

mux/demux modules  
 bands supported [1-14](#)  
 configurations [1-16](#)

meshed ring topologies and [5-45](#)

See also 4-channel mux/demux modules; 8-channel mux/demux modules; 32-channel mux/demux modules; add/drop mux/demux modules; mux/demux cabling; terminal mux/demux modules

mux/demux motherboards

description [1-13](#)

shelf configuration rules [3-1](#)

---

## N

network management

comparison (table) [1-22](#)

description [1-20](#)

in-band message channel [1-20](#)

NME [1-21](#)

network management Ethernet

See NME

NME

description [1-21](#)

---

## O

OC-1

client interface support [1-7](#)

OC-24

client interface support [1-7](#)

OFC

client signal encapsulation types supported [1-7](#)

open fiber control. See OFC

optical link loss

2.5-Gbps line card motherboards [4-4](#)

10-Gbps line card motherboards [4-5](#)

cross connect drawers [4-6](#)

data channels [4-4](#)

hubbed ring topologies with line card protection, example [5-34](#)

hubbed ring topologies with splitter protection, example [5-23](#)

meshed ring topologies and [5-45](#)

meshed ring topologies with line card protection, example [5-55](#)

meshed ring topologies with unprotected channels, line card protected, example [5-70](#)

meshed ring topologies with unprotected channels, splitter protected, example [5-65](#)

meshed ring with splitter protection, example [5-46](#)

OSC [4-6](#)

point-to-point topologies with line card protection, example [5-18](#)

point-to-point topologies without protection, example [5-10, 5-12, 5-13](#)

point-to-point topologies with splitter protection, example [5-16](#)

PSMs [4-6](#)

See also optical power budgets

optical mux/demux modules. See mux/demux modules

optical power budgets

line card protected configurations [5-6](#)

overall [4-2](#)

splitter protected configurations [5-4, 5-5, 5-7](#)

trunk fiber protected configurations [5-8](#)

unprotected configurations [5-2, 5-3](#)

optical supervisory channel. See OSC

OSC

description [1-14, 1-21](#)

information types [1-14](#)

optical link loss [4-6](#)

optical link loss through mux/demux modules [4-6](#)

receiver sensitivity (table) [4-2](#)

transmit power (table) [4-2](#)

---

## P

Peer-to-Peer Remote Copy. See PPRC

point-to-point topologies

configuring line card protection [5-17 to 5-21](#)

configuring splitter protection [5-15 to 5-17](#)

configuring without protection [5-13 to 5-15](#)

description [2-6](#)  
 equipment for [5-9](#)  
 multiple trunk support [2-12](#)  
 optical power budgets for line card protected  
   16-channel [5-18](#)  
 optical power budgets for protected 8-channel [5-12](#)  
 optical power budgets for splitter protected 32  
   channel [5-16](#)  
 optical power budgets for unprotected 16-channel [5-10](#)  
 optical power budgets for unprotected 32-channel [5-13](#)  
 protection in [2-6](#)

power supplies

  description [1-1](#)

PPRC

  client interface support [A-2](#)  
   description [A-4](#)

processor cards

  description [1-19](#)  
   features [1-19](#)

processors. See processor cards

protection

  description [1-3](#)  
   levels of [2-1](#)  
   ring topologies [2-10](#)  
   types [2-1 to 2-4](#)  
   See also APS; client protection; line card protection;  
   splitter protection; y-cable protection

PSMs

  description [1-18](#)  
   example configuration (figure) [5-8](#)  
   optical link loss [4-6](#)  
   receiver ranges [4-2](#)  
   transmit power [4-2](#)  
   trunk fiber based protection [2-5](#)

---

## R

receiver sensitivity table [4-2](#)  
 redundancy  
   processor cards [1-20](#)  
 ring topologies  
   multiple trunk support [2-12](#)  
   protection in [2-10 to 2-12](#)  
   shelf configuration rules [3-8](#)  
   See also hubbed ring topologies; meshed ring topologies

---

## S

SANs  
   IBM environment [A-1](#)

SDH

  client interface support [1-5](#)  
   configuring protocol monitoring [1-9](#)

selectable transceivers

  description [1-7](#)

SFP optics

  description [1-7](#)

shelf configuration examples

  cross connect drawer cabling in line card protected  
     configurations [5-7](#)  
   cross connect drawer cabling in splitter protected  
     configurations [5-5](#)  
   cross connect drawer cabling in unprotected  
     configurations [5-3](#)  
   direct cabling in line card protected configurations [5-6](#)  
   direct cabling in splitter protected configurations [5-4](#)  
   direct cabling in unprotected configurations [5-2](#)  
   hubbed ring topologies with line card protection [5-35,](#)  
     [5-37, 5-39, 5-41, 5-43](#)  
   hubbed ring topologies with splitter protection [5-24,](#)  
     [5-26, 5-28, 5-30, 5-32](#)  
   meshed ring topologies with line card protection [5-56,](#)  
     [5-58, 5-60, 5-62](#)  
   meshed ring topologies with splitter protection [5-47,](#)  
     [5-49, 5-51, 5-53](#)

- meshed ring topologies with unprotected channels, line card protected [5-71, 5-73](#)
- meshed ring topologies with unprotected channels, splitter protected [5-66, 5-68](#)
- point-to-point topologies with line card protection, 16 channels [5-18](#)
- point-to-point topologies with line card protection, 32 channels [5-20](#)
- point-to-point topologies without protection [5-11, 5-13, 5-14](#)
- point-to-point topologies with splitter protection [5-16](#)
- shelf configuration rules
  - 4-channel mux/demux modules [3-2 to 3-4](#)
  - 8-channel mux/demux modules [3-2 to 3-4](#)
  - mux/demux motherboards [3-1](#)
  - ring topologies [3-8](#)
- single-mode fiber
  - other supported client signal encapsulations [1-7](#)
  - supported IBM storage protocols [1-6](#)
- SM fiber. See single-mode fiber
- SONET
  - client interface support [1-5](#)
  - configuring protocol monitoring [1-9](#)
- splitter motherboards. See line card motherboards
- splitter protected configuration
  - examples [5-4 to 5-5](#)
- splitter protection
  - 4-channel mux/demux modules and [3-3](#)
  - 8-channel mux/demux modules and [3-3](#)
  - configuring hubbed ring topologies [5-22 to 5-33](#)
  - configuring meshed ring topologies [5-46 to 5-54](#)
  - configuring meshed ring topologies with unprotected channels [5-64 to 5-69](#)
  - configuring point-to-point topologies [5-15 to 5-17](#)
  - considerations [2-2](#)
  - cross connect drawer cabling, example [5-5](#)
  - description [2-1](#)
  - direct cabling, example [5-4](#)
  - scheme (figure) [2-2](#)
- storage area networks. See SANs

Synchronous Digital Hierarchy. See SDH

Sysplex Timer

- client interface support [1-6](#)

- IBM storage environment and [A-3](#)

system

- components [1-4 to 1-20](#)

- functional overview [1-3](#)

system management

- OSC and [1-14](#)

---

## T

terminal mux/demux modules

- description [1-16](#)

- optical link loss [1-16](#)

- transponder placement with [3-5](#)

See also 32-channel mux/demux modules

theory of operation [1-3](#)

topologies. See bus topologies; hubbed ring topologies; meshed ring topologies; point-to-point topologies

Topology [2-8](#)

transceivers. See SFP optics

transmitter launch power

- data channels [4-2](#)

- OSC [4-2](#)

transponder modules

- 2.5-Gbps line card motherboards [1-12](#)

- 10-Gbps line card motherboards [1-13](#)

- description [1-4](#)

- interfaces [1-4](#)

- line card protection and [3-6](#)

- shelf rules [3-5](#)

- Type 1 [1-4](#)

- Type 2 [1-7](#)

trunk fiber protected configuration

- examples [5-8](#)

trunk fiber protection  
  considerations [2-5](#)  
  description [2-5](#)  
  scheme (figure) [2-5](#)

trunk side interfaces  
  description [1-4](#)

---

## U

Unidirectional Path Switched Ring. See UPSR

unidirectional path switching  
  description [2-10](#)  
  example (figure) [2-12](#)  
  normal state (figure) [2-11](#)

unprotected channels  
  adding [5-63](#)  
  configuring in meshed ring topologies [5-64 to 5-74](#)

unprotected configurations  
  cross connect drawer cabling, example [5-3](#)  
  direct cabling, example [5-2](#)  
  examples [5-1 to 5-3](#)

unprotected topologies. See point-to-point topologies

UPSR  
  description [2-10](#)

---

## X

XRC  
  client interface support [A-2](#)  
  description [A-4](#)

---

## Y

y-cable protection  
  considerations [2-3](#)  
  description [2-3](#)