

Cisco 7000 Processors

Cisco 7000 processors provide new functionality and have different names than the interface cards used in other Cisco routers.

Table E-1 provides general conversion information. For example, the RP card on the Cisco 7000 provides the same general area of functionality as the CSC-MC+ and CSC-ENVM cards on other Cisco routers.

Table E-1 Interface Processor Conversion Table

Modular Products		
Card	Cisco 7000 Processors	Cisco 7000 Processor Options
CSC/4	RP (Route Processor)	
CSC-ENVM	RP (Route Processor)	
CSC-MC+	RP (Route Processor)	
CSC-CCTL2	SP (Switch Processor)	
CSC-C2MEC	EIP (Ethernet Interface Processor)	
	CX-EIP2	2 ports
	CX-EIP4	4 ports
	CX-EIP6	6 ports
CSC-C2CTR	TRIP (Token Ring Interface Processor)	
	CX-TRIP4	4 ports
CSC-C2FCI(T)	FIP (FDDI Interface Processor)	
	CX-FIP-MM	Multimode-to-multimode
	CX-FIP-SS	Single mode-to-single mode
	CX-FIP-MS	Multimode-to-single mode
	CX-FIP-SM	Single mode-to-multimode
CSC-SCI	FSIP (Fast Serial Interface Processor)	4 or 8 ports available for RS-232, RS-449, RS-530, V.35, and X.21
CSC-HSCI	HIP (HSSI Interface Processor)	

