



---

## Symbols

- .bin file
  - downloading from CCO [3-4](#)
  - to recover system software [3-4](#)
- .pax file
  - upgrading system software [3-1](#)
- @ symbol to start boot sequence [3-4](#)

---

## A

- administrator [2-2](#)
- agent lists
  - creating [2-5](#)
- agents
  - content routing [2-7](#)
- alias command [C-2](#)
- annealing [C-6](#)
- autosense command [C-3](#)

---

## B

- bandwidth command [C-4](#)
- bloat command [C-5](#)
- boomerang command [C-6, C-7, C-9, C-10](#)
- boomerang database command [C-8](#)
- boomerang send-packet command [C-11](#)
- booting
  - Content Router [2-2](#)
- browser [2-7](#)

---

## C

- caching
  - disabling for certain clients [A-9](#)
- cautions
  - description of [xiv](#)
- check command [C-13](#)
- checking and repairing
  - DOS file system volumes [3-8](#)
- clear command [C-14](#)
- client command [C-16](#)
- client-group command [C-18](#)
- client list configuration
  - commands [B-11](#)
  - mode [B-3](#)
- client lists
  - creating [2-5](#)
- clock command [C-19](#)
- clock timezone command [C-20](#)
- command
  - syntax [B-3](#)
- commands
  - client list configuration [B-11](#)
  - domain configuration [B-10](#)
  - EXEC [B-4](#)
  - global configuration [B-7](#)
  - interface global configuration [B-9](#)
  - WCCP Version 2 [A-14](#)
- configuration
  - Content Router software [2-1](#)
  - content routing agents [2-7](#)
  - direct mode [2-4](#)
  - domains [2-6](#)

- information required 2-2
- performing a basic startup configuration 2-1
- required information 2-2
- samples 3-9
- saving configuration changes B-4
- service group A-8
- WCCP mode 2-4
- configure command C-21
- console command
  - show cron C-79
- Content Router
  - communication with router A-4
  - maintaining disks 3-6
  - recovering
    - lost password 3-8
    - system software 3-4
  - repartitioning disks 3-7
  - sample configurations 3-9
  - upgrading system software 3-1
- content routing agents
  - configuring 2-7
- conventions
  - document xiii
- copy command C-22
- cpfile command C-23
- cron command C-24
- customer service and support xv to xviii

---

## D

- debug command C-25
- default gateway 2-3
  - setting 2-2
- del command C-26
- deltree command C-27
- denial of service attacks
  - prevention C-74
  - syslog warning C-75
- dir command C-28

- direct mode 2-4
  - configuration 2-4
- disable command C-29
- disabling
  - caching for certain clients A-9
- disk command C-30
- disk-partitions command 3-6
- disks
  - checking and repairing DOS file system volumes 3-8
  - configuring C-30
  - maintenance 3-6
  - repartitioning 3-7
- displaying WCCP settings A-12
- DNS race 1-1
- DNS race winner database C-8
- dns-ttl command C-32
- documentation
  - conventions xiii
  - ordering xvi
- domain configuration mode B-2
- domains
  - configuring 2-6
- DOS file system (dosfs)
  - checking and repairing volumes 3-8
  - maintaining 3-6
- dosfs command C-33

---

## E

- enable command C-35
- end command C-36
- exception debug command C-37
- EXEC
  - commands B-4
  - mode B-1
- exec-timeout command C-38
- exit command C-39

---

**F**

## failure

- power [3-4](#)

## Flash memory

- recovering [3-4](#)

fragment-size command [C-40](#)fullduplex command [C-41](#)


---

**G**

## global configuration

- commands [B-7](#)

- mode [B-2](#)

---

**H**
halfduplex command [C-42](#)

## help

- system [B-4](#)

help command [C-43](#)

## home router

- setting [2-2](#)

hostname command [C-44](#)hot spot handling [A-5](#)


---

**I**
inetd command [C-45](#)

## initializing

- Content Router software [2-2](#)

install command [C-46](#)interface command [C-47](#)

## interface global configuration

- commands [B-9](#)

- mode [B-2](#)

## IP address

- setting [2-2](#)

## ip command

- global configuration mode [C-49](#)

- interface configuration mode [C-48](#)

ip-ttl command [C-51](#)

## ip wccp command

- description [A-16](#)

- enabling Content Router support [2-4](#)

ip wccp group-listen command [A-18](#)

## ip wccp redirect command

- enabling web traffic redirection [2-4](#)

ip wccp redirect exclude in command [A-19](#)ip wccp redirect out command [A-20](#)ip wccp version command [A-21](#)


---

**K**
key command [C-52](#)


---

**L**
load balancing [A-5](#)load shedding [A-5](#)logging command [C-54](#)

## lost password

- recovering [3-8](#)

ls command [C-56](#)


---

**M**

## maintaining

- Content Router disks [3-6](#)

max-propagation-delay command [C-57](#)MIB [C-117](#)mkdir command [C-58](#)mkfile command [C-59](#)

## mode

- client list configuration [B-3](#)

- direct [2-4](#)

domain configuration [B-2](#)  
 EXEC [B-1](#)  
 global configuration [B-2](#)  
 interface global configuration [B-2](#)  
 WCCP [2-4](#)  
 multiple router support [A-2](#)

---

## N

Network Time Protocol  
   configuring [C-64](#)  
 no command  
   boomerang configuration mode [C-62](#)  
   global configuration command [C-61](#)  
   interface configuration mode [C-60](#)  
 no debug command [C-63](#)  
 ntp command [C-64](#)  
 ntpdate command [C-65](#)

---

## O

operating system  
   booting [2-2](#)  
 origin-server command [C-66](#)

---

## P

password  
   administrator [2-2](#)  
   recovering lost [3-8](#)  
   setting [A-9](#)  
 ping command [C-67](#)  
 power  
   failure [3-4](#)  
 pwd command [C-68](#)

---

## R

reboot [2-2](#)  
 recovering  
   lost password [3-8](#)  
   system software [3-4](#)  
 reload command [C-69](#)  
 rename command [C-70](#)  
 repairing  
   DOS file system volumes [3-8](#)  
 repartitioning Content Router disks [3-7](#)  
 rmdir command [C-71](#)  
 router  
   communication with Content Router [A-4](#)  
   registering a router to a multicast address [A-8](#)

---

## S

server-delay command [C-72](#)  
 service and support [xv to xviii](#)  
 service group  
   configuring using WCCP Version 2 [A-8](#)  
 setting password [A-9](#)  
 show arp command [C-73](#)  
 show boomerang command [C-74](#)  
 show clock command [C-78](#)  
 show commands [B-11](#)  
 show cron command [C-79](#)  
 show debugging command [C-80](#)  
 show disk-partitions command [3-6, C-81](#)  
 show disks command [3-6, C-82](#)  
 show dosfs volumes command [3-7](#)  
 show events command [C-83](#)  
 show file-descriptors command [C-84](#)  
 show flash command [C-85](#)  
 show hardware command [C-86](#)  
 show hosts command [C-87](#)  
 show inetd command [C-88](#)  
 show interface command [C-89](#)

show ip interface command [A-22](#)  
     showing interface statistics [2-4](#)  
 show ip routes command [C-91](#)  
 show ip wccp command [A-15, A-25](#)  
     showing statistics [2-4](#)  
 show logging command [C-92](#)  
 show memory command [C-93](#)  
 show ntp command [C-94](#)  
 show processes command [C-95](#)  
 show running-config command [A-9, C-97](#)  
 show snmp command [C-99](#)  
 show stacktrace command [C-101](#)  
 show startup-config command [C-102](#)  
 show statistics command [C-104](#)  
 show tcp command [C-105](#)  
 show tech-support command [C-106](#)  
 show tftp-server command [C-107](#)  
 show transaction-logging command [C-108](#)  
 show trusted-hosts command [C-109](#)  
 show user command [C-110](#)  
 show users command [C-111](#)  
 show version command [3-6, C-112](#)  
 show wccp command [C-113](#)  
 simulated annealing [1-1](#)  
 SNMP  
     MIB [C-117](#)  
 snmp-server community command [C-114](#)  
 snmp-server contact command [C-115](#)  
 snmp-server enable command [C-116](#)  
 snmp-server enable traps command [C-116](#)  
 snmp-server host command [C-117](#)  
 snmp-server location command [C-118](#)  
 software  
     configuring [2-1](#)  
     initializing [2-2](#)  
     recovering [3-4](#)  
     upgrading [3-1](#)  
 statistics  
     Content Router [C-104](#)

subnet mask  
     setting [2-2](#)  
 system help [B-4](#)  
 system software  
     maintaining [3-1](#)  
     recovering [3-4](#)  
     upgrading [3-1](#)

---

## T

tclsh command [C-119](#)  
 tcp command [C-120](#)  
 terminal [C-122](#)  
 terminal command  
     EXEC mode [C-122](#)  
     global configuration mode [C-123](#)  
 tftp-server command [C-124](#)  
 transaction-log force command [C-125](#)  
 transaction-logs command [C-126](#)  
 trusted-host command [C-132](#)  
 type command [C-133](#)

---

## U

undebug command [C-134](#)  
 upgrading system software [3-1](#)  
 user command [C-135](#)

---

## V

verifying  
     software configuration [2-7](#)  
     WCCP configuration settings [A-9](#)

---

## W

### WCCP

displaying settings [A-12](#)

mode [2-4](#)

#### Version 2

commands [A-14](#)

configuring a service group [A-8](#)

operation [A-2](#)

overview [A-2](#)

prerequisites [A-7](#)

restrictions [A-5](#)

verifying configuration settings [A-9](#)

wccp dns-boomerang router-list-num command [C-137](#)

wccp flow-redirect command [C-138](#)

#### WCCP mode

temporarily disabling boomerang [2-5](#)

wccp port-list command [C-139](#)

wccp router-list command [C-140](#)

wccp shutdown command [C-141](#)

wccp slow-start command [C-142](#)

wccp version command [C-143](#)

whoami command [C-144](#)

write command [C-145](#)