



## Technical Specifications

This appendix provides the technical specifications for the Cisco CTE 1400. Power, physical, and environmental specification are listed in [Table A-1](#).

**Table A-1** *Technical Specifications*

<b>Power<sup>1</sup></b>	
AC power supply:	
Wattage	125W
Voltage	100 to 240 VAC, 3.6–1.8 A, 60 to 50 Hz
System battery	CR2032 3-V lithium coin cell
<sup>1</sup> Under typical line conditions and over the entire system ambient operating range, the inrush may read 45 A per installed power supply.	
<b>Physical</b>	
Rack Mount (1U):	
Height	1.7 inches (4.3 cm)
Width	16.7 inches (42.5 cm)
Depth	22 inches (55 cm)
Weight	23 lb (10 kg) maximum

NOTE: For the full name of an abbreviation or acronym used in this table, see the glossary.

*Table A-1 Technical Specifications (continued)*

<b>Environmental</b>	
<b>Temperature:</b>	
Operating	50 to 95°F (10 to 35°C)
Storage	-40 to 149°F (-40 to 65°C)
<b>Relative humidity:</b>	
Operating	8 to 80% (noncondensing) with a humidity gradation of 10% per hour
Storage	5 to 95% (noncondensing)
<b>Maximum vibration:</b>	
Operating	0.25 G (half-sine wave) at a sweep of 3 to 200 Hz for 15 minutes
Storage	0.5 G at 3 to 200 Hz for 15 minutes
<b>Maximum shock:</b>	
Operating	Six consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 41 G for up to 2 ms
Storage (non-operational)	Six consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 71 G for 2 ms
<b>Altitude:</b>	
Operating	-50 to 6,500 ft (-16 to 2000 m)
Storage	-50 to 35,000 ft (-16 to 10,600 m)

NOTE: For the full name of an abbreviation or acronym used in this table, see the glossary.