



Symbols

\$MGMTPORTNO [9-5](#)

\$SSLPORTNO [9-5](#)

\$ subattributes [C-13](#)

\$ variables, in start scripts [9-5](#)

A

AAA

See RADIUS

aaa.properties file [5-6, C-19, D-1, D-4](#)

aaa.xml [D-1, D-2](#)

aaaFilename attribute [D-4](#)

AAA MBean [5-10](#)

access accept messages [C-13](#)

access control lists

See ACLs

access reject messages [13-9](#)

Account-Info, Demo mode [C-13](#)

accounting

RADIUS [C-1, C-16](#)

solutions [C-16](#)

ACLs [10-12](#)

Advanced Firewall page [10-16, 10-22](#)

established keyword in [10-20](#)

format in CDAT [10-26](#)

generated [10-19](#)

My Firewall page [10-19, 10-21](#)

numbers [10-23, 10-26, 10-27](#)

priorities [10-23](#)

RADIUS profiles [C-9, C-15](#)

restrictions [10-26](#)

viewing in CDAT [10-19](#)

addDimension call [5-14](#)

addHandler [4-2](#)

addListener [4-6, 4-7](#)

Add Services option [2-14](#)

AddWebApplication [4-5](#)

administrative firewalls [10-25](#)

Advanced Firewall page [10-16](#)

advertisingCaptiveDuration attribute [11-12, 11-18](#)

advertisingCaptiveOn attribute [11-11, 11-24](#)

advertisingCaptivePort attribute [11-12](#)

advertisingCaptiveURL attribute [11-11](#)

advertising redirection

configuring [2-17, 11-11, 11-15, 11-22](#)

duration [2-17](#)

hobbies [11-8, 11-16](#)

HTTP query parameters [11-3](#)

port [2-17](#)

profile attributes [C-12](#)

Agent View

accessing [3-4, 3-6](#)

description [3-3, 3-4](#)

links on CDAT main window [2-19, 3-7](#)

URLs [3-6](#)

using [3-8](#)

AllApplicationsDescriptions attribute [5-13](#)

Allow Clear Text Passwords [B-3](#)

allowedClients attribute [7-6, D-5](#)

AllProtocolDescriptions attribute [5-12](#)

alternative configurations, captive portal [11-5](#)

alwaysGetAllAttributes attribute [8-2](#)

apidoc [2-20](#)

APIs

- SESM 5-19
- APN C-11
- append attribute 4-3, 4-5
- application.home 4-4, 4-5, 5-3, 9-5
- application.log 4-5, 5-3, 13-4
- application.portno 9-5
- application.ssl.portno 9-5
- applications
 - startup scripts 9-3
 - stopping 9-6
- applications list, on firewall pages 5-11, 5-13, 10-17, 10-18
- Apply button, AgentView 3-11
- attributes, arbitrary
 - configuring 10-10
 - demonstrating 10-11
 - description 10-5, 10-9
 - URL 10-11
- attributes, configuration
 - changing values 3-2
 - persisting changes 3-11
- attributes, RADIUS
 - defining new 7-4, C-3, C-5, D-2, D-4
 - defining new in RDP 7-4
 - dictionary C-2
 - predefined C-3
- authAttributes attribute 7-5
- authentication
 - multikey 7-5, 10-28
 - NDS B-3
 - RDP 7-8
 - setting RADIUS port C-1
 - type C-7
- AuthInfo attribute 3-5
- autoConnect attribute 5-5
- automatic connections
 - configuring 10-1, C-12
 - description 10-1
 - disconnecting 10-3
 - RADIUS configuration example C-15

- RDP 5-5
- self-care, LDAP mode 10-3
- status 10-2
- troubleshooting 10-2
- autopolicing 10-28

B

- blocked services C-14
- branding 5-9, 10-4
- BUNDLE_LENGTH attribute 5-8, 5-9, 12-2
- bundled RADIUS server D-1
- burst rates C-8, C-13

C

- cacheExpireInterval 8-3
- cacheMinFreeMem 8-2
- cacheObjectTimeout 8-3
- cacheSessionTimeout 8-3
- caching
 - cache size 8-2
 - directory data 8-2
 - memory usage 8-2
 - profiles 5-5
 - RDP 10-3
 - SESM 5-5
 - SPE attributes 8-2
- captiveportal.jetty.xml 3-14
- captiveportal.xml 3-14, 11-10, 11-11, 11-24
- Captive Portal application
 - alternatives 11-5
 - benefits 11-5
 - configuring 11-11
 - description 11-3
 - installing 2-15
 - IP address 2-15
 - ports 2-15

- running secure mode [A-4](#)
- captiveportal MBean [11-11](#)
- captive portal solution
 - alternative configurations [11-5](#)
 - configuration files [3-18](#)
 - diagram [11-2](#)
 - eliminating J2EE listeners [11-5](#)
 - eliminating redirection types [11-5](#)
 - example profiles [11-8](#)
 - groups [11-19](#)
 - installing [2-7, 11-6](#)
 - NWSP role [11-4](#)
 - required Cisco IOS releases [11-1](#)
 - startup scripts [11-9](#)
 - troubleshooting [11-23](#)
- CDAT
 - configuring [6-1](#)
 - cookies [6-1](#)
 - entering ACLs [10-26](#)
 - installing [2-7, 2-19](#)
 - links on main window [2-19, 6-3](#)
 - logging in [6-3, 6-5](#)
 - logging on [8-3](#)
 - main window [3-6, 3-7](#)
 - MBean [6-3](#)
 - port number [2-19](#)
 - session tuning [6-3](#)
 - starting [9-3](#)
 - stopping [9-6](#)
 - timeouts [6-4](#)
 - viewing generated ACLs [10-19](#)
 - virtual memory [8-2](#)
- cdat.jetty.xml [4-2](#)
- cdat.xml [3-15, 6-1](#)
- certificates
 - keystore [A-2](#)
 - SESM license [2-1](#)
- CHAP [C-7](#)
- Cisco Access Registrar [C-17](#)
- Cisco-AVpairs [C-9, C-15](#)
- Cisco IOS, required releases
 - captive portal features [11-1](#)
 - complete ID [10-4](#)
 - port-bundle host key [F-2](#)
 - TCP redirect commands [11-7](#)
- Clear Text Passwords [B-3](#)
- clients
 - RADIUS server [12-5, C-1](#)
 - RDP [2-14, 2-15](#)
 - restricted for bundled RADIUS server [D-5](#)
 - restricted for RDP [7-6](#)
 - SSG subnets [2-9](#)
- Client subnet attribute [2-9](#)
- cn [2-12, 5-6, 6-3, B-2](#)
- comments, in MBeans [3-11](#)
- common name
 - See cn
- complete ID [10-4, 10-5, 10-8](#)
- compressed images [2-2](#)
- concurrent services [C-7](#)
- config.xml [12-9](#)
- ConfigAgent [3-1, 3-16, 3-17, 5-19](#)
- configuration files
 - customizing [5-20](#)
 - DTD [3-15](#)
 - editing [3-14](#)
 - MBean [3-1](#)
 - names [3-14](#)
 - path names in web.xml [13-8](#)
 - See also J2EE; MBeans
- confirmAtAccountLogoff attribute [5-14](#)
- confirmAtServiceLogoff attribute [5-14](#)
- confirmAtServiceLogon attribute [5-14](#)
- confirmMutexDisconnect attribute [5-5](#)
- connections
 - See automatic connections;services; directory
- Connection MBean [8-3](#)
- connectionNameRoot attribute [8-2](#)

- console
 - installation mode [2-4](#)
 - iPlanet [B-6](#)
 - management [2-8, 3-5](#)
 - NDS (ConsoleOne) [B-2, B-3](#)
 - constructing MBeans [3-17](#)
 - containers
 - directory [2-12, 8-2, 12-8](#)
 - for port-bundle host key [4-1](#)
 - Jetty [4-2](#)
 - other than Jetty [4-2](#)
 - See J2EE containers
 - WAR files [4-2](#)
 - See also J2EE; Jetty server
 - content applications [11-4](#)
 - context
 - attribute [8-2](#)
 - directory [12-8](#)
 - iPlanet and Sun ONE [B-4](#)
 - NDS [B-1](#)
 - path attribute [4-5](#)
 - cookies [6-1, C-8](#)
 - core model [2-7](#)
 - CPDURATION query parameter [11-3, 11-18](#)
 - CPSUBSCRIBER query parameter [11-3, 11-25](#)
 - CPURL query parameter [11-3](#)
 - CPU utilization [9-7](#)
 - credentialMaxLength attribute [5-14](#)
 - credentials attribute, SPE [8-3](#)
 - customApplications attribute [5-12](#)
 - custom installations [2-7](#)
 - customizing applications [2-20](#)
 - customProtocols attribute [5-12](#)
-
- D**
- debug attribute [4-4, 5-2](#)
 - debugging [4-3, 5-2, 13-4](#)
 - Debug MBean [4-4](#)
 - debugPatterns attribute [4-4, 5-2](#)
 - debugThreads attribute [5-3](#)
 - debugVerbosity attribute [5-3](#)
 - defaultDuration attribute [11-15, 11-18](#)
 - default network [F-2](#)
 - defaultPage attribute [11-15](#)
 - defaultURI attribute [5-14, 11-17](#)
 - defaultURL attribute [11-15](#)
 - defineServiceRedirect attribute [11-12](#)
 - demo data file [11-14](#)
 - demoDataFile attribute [5-6](#)
 - Demo mode
 - attributes [5-4](#)
 - blocked services [C-14](#)
 - data [5-6](#)
 - installing [2-7](#)
 - profiles [C-13](#)
 - self-subscription [C-13](#)
 - single sign-on [C-14](#)
 - switching to [5-4](#)
 - demos
 - arbitrary attributes [10-11](#)
 - location awareness [10-8](#)
 - deployer-imposed firewalls [10-12, 10-25](#)
 - deployment modes, switching [2-7](#)
 - DESS
 - configuration file [3-15](#)
 - dessauth.xml [3-15, 6-1, 8-1](#)
 - DESSMode MBean [5-6, 11-14](#)
 - DESSPrincipal attribute, SPE [8-2](#)
 - DESSusecasedata.ldf file [8-4](#)
 - destination
 - service [C-7](#)
 - URL [11-9](#)
 - dictionary, RADIUS [C-2](#)
 - direction attribute [5-13](#)
 - directory
 - caching [8-2](#)
 - configuring for SESM [B-1](#)

connection information [2-11, 8-3](#)
 container [2-12, 8-2, 12-8](#)
 context [12-8](#)
 extending schema [2-19, 8-3](#)
 failover [8-3](#)
 installation results [2-20](#)
 IP address [2-11, 8-3, 12-8](#)
 logging activity [8-2](#)
 meta schema [2-12](#)
 organization [2-12, 12-8](#)
 password [2-11, 8-3](#)
 portal communication [12-9](#)
 ports [2-11, 8-3, 12-8](#)
 RDP communication [12-8](#)
 running during SESM install [1-6](#)
 sample data [8-4](#)
 user ID [2-11, 8-3, 12-8](#)
 Directory MBean [8-2](#)
 disconnecting autoconnect services [10-3](#)
 disconnectWhenUnsubscribe attribute [5-14](#)
 disk space [1-2](#)
 displayApplications attribute [5-13](#)
 distinguished name
 See dn
 dn [2-12, 5-6, 6-3](#)
 DNS [C-7](#)
 domain names [C-7](#)
 downloading SESM [2-2](#)
 DTD [3-15](#)
 dump attribute [7-5, D-4](#)
 duplicate locations [10-5, 10-6](#)
 duration
 advertising redirection [2-17, 11-22](#)
 initial logon redirection [2-17](#)
 parameters [11-17](#)
 in Cisco IOS commands [11-22, 11-23](#)
 in HTTP requests [11-3](#)
 in RADIUS profiles [C-12](#)
 timing of [11-4](#)

dynamic attribute definitions [C-5](#)
 dynamicAttributes attribute [7-4, D-4](#)

E

edge session, SSG [C-11](#)
 editing configuration files [3-14](#)
 encryption [A-2](#)
 erp.xml [7-3, D-1, D-3](#)
 error redirections [2-16](#)
 errorURL attribute [11-13](#)
 established keyword, in ACLs [10-20](#)
 evaluation licenses [2-6](#)
 example
 captive portal profiles [11-8](#)
 service group profiles [C-10](#)
 service profiles [C-9](#)
 subscriber profiles [C-15](#)
 examples
 ACLs [10-21, 10-23](#)
 profiles [C-19](#)
 exceptions, out of memory [9-8, 13-9](#)
 executables
 adding Windows services [9-7](#)
 installation [2-2](#)
 startup scripts [9-1](#)
 stop scripts [9-6](#)
 explicit IP address, SSG [5-9](#)
 extended access control lists [10-12](#)
 See also ACLs
 extending directory schema [2-19, 8-3](#)

F

factory attribute [8-2](#)
 failover, LDAP directory [8-3](#)
 features
 configuring [10-1](#)

filename attribute, in Log MBean 4-4

files

- .iss 2-4
- .properties 2-4
- aaa.properties 5-6, C-19, D-1, D-4
- aaa.xml D-1, D-2
- captiveportal.jetty.xml 3-14
- captiveportal.xml 3-14, 11-10, 11-11, 11-24
- cdat.jetty.xml 4-2
- cdat.xml 3-15, 6-1
- dessauth.xml 3-15, 6-1, 8-1
- DESS configuration file 3-15
- DESSusecasedata.ldf 8-4
- erp.xml 7-3, D-1, D-3
- installation image names 2-1, 2-2
- installation results 2-20
- J2EE configuration 3-18
- keystore A-2
- lib.xml 6-1
- licensenum.txt 2-6
- MBean configuration 3-1
- messageportal.xml 3-14, 11-13, 11-15
- nwsp.jetty.xml 3-14, 4-2
- nwsp.xml 3-14, 5-2, 11-16
- pda.jetty.xml 3-14
- pda.xml 3-14, 5-2
- rdp.xml 3-14, 7-3
- README.SESM.LDIF.html 2-20
- ssgconfig.txt 11-7
- startup scripts 9-3
- wap.jetty.xml 3-14
- wap.xml 3-14, 5-2
- WAR 4-2
- web.xml 2-20, 3-18
- web.xml file 13-8
- webdefault.xml 3-18
- webdefaults.xml 3-18
- web-jetty.xml 2-20, 3-19, 4-2
- xmlconfig.dtd 3-15

See also logs

Firewall MBean 5-11

firewalls

- administrative 10-25
- Advanced Firewall page 10-16
- applications list 5-11, 5-12, 5-13, 10-17, 10-18
- configuring 10-18
- deployer-imposed 10-12, 10-25
- description 10-12
- established keyword 10-20
- generated ACLs 10-19
- My Firewall page 10-14
- priorities 10-13
- protocols 5-11, 5-12
- subscriber experiences 10-25
- viewing ACLs in CDAT 10-19
- See also ACLs

frames C-8, C-12

frequency, in advertisement redirections 11-22, C-12

full name, in service profiles C-8

G

generated ACLs 10-19

generic start script 9-4, A-3

global attributes, SSG 5-7, 5-16

greetings page

See initial logon redirection

group password

See service groups

groupPassword attribute 7-5

groups

captive portal 11-5, 11-7, 11-19

GUI installation mode 2-3

H

handler attribute 7-5, D-4

- handlers
 - port-bundle host key [4-2](#)
 - RDP [7-1, 7-8](#)
 - hardware platforms [1-1](#)
 - hierarchical policing [10-28, C-8, C-13](#)
 - hobbies, captive portal advertisement [11-8, 11-14, 11-16](#)
 - home
 - application [9-5](#)
 - JDK [1-4](#)
 - jetty [9-5](#)
 - home page, URLs [C-12](#)
 - host attribute [11-11](#)
 - HTML Adaptor server [3-3, 3-5](#)
 - HTML frames [C-8, C-12](#)
 - HTTP
 - configuring listener port [2-8](#)
 - errors [13-4](#)
 - mode, removing [A-3](#)
 - processing requests [11-2](#)
 - redirections [2-16, 11-3](#)
 - request log [13-4](#)
 - SocketListener [4-6, 4-7](#)
 - Version 1.1 [11-25](#)
 - HTTPS
 - description [A-2](#)
 - keystore [4-7](#)
 - keystore file [A-2](#)
 - running secure-only mode [A-3](#)
 - HttpServer MBean [4-5](#)
-
- idle timeout
 - services [C-7](#)
 - sessions [C-11](#)
 - ignoreProfile attribute [11-15](#)
 - images
 - downloading installation [2-2](#)
 - referenced in JSPs [5-20](#)
 - inacls [10-16, 10-22](#)
 - inetorgPerson attribute [2-12](#)
 - initialCaptiveDuration attribute [11-12, 11-18](#)
 - initialCaptiveOn attribute [11-11, 11-24](#)
 - initialCaptivePort attribute [11-12](#)
 - initialCaptiveURL attribute [11-11](#)
 - initializing MBeans [3-17](#)
 - initial logon redirection
 - configuring [2-17, 11-11, 11-15, 11-22](#)
 - duration [2-17](#)
 - HTTP query parameters [11-3](#)
 - port [2-17](#)
 - profile attributes [C-12](#)
 - initial URL [10-11](#)
 - installing
 - captive portal solution [2-7, 2-15, 11-6](#)
 - CDAT [2-7, 2-19](#)
 - custom [2-7](#)
 - Demo mode [2-7](#)
 - directory [2-6](#)
 - image for [2-1](#)
 - individual components [2-7](#)
 - iPlanet [B-4](#)
 - JDK [1-5](#)
 - JRE [1-3](#)
 - license [2-6](#)
 - logging during [2-5](#)
 - Message Portal application [2-15](#)
 - modes [2-3](#)
 - NDS [B-1](#)
 - NWSP [2-8](#)
 - PDA [2-8](#)
 - portal applications [2-7](#)
 - prerequisites [1-1](#)
 - RDP [2-7, 2-13](#)
 - results [2-20, 11-6](#)
 - SESM components [2-7](#)
 - SPE [2-7](#)
 - Sun ONE [B-4](#)

temporary disk space for [1-2](#)
 typical [2-7](#)
 WAP [2-8](#)
 WSG [2-7](#)

interestPages attribute [11-16](#)
 interests attribute [11-14, 11-16](#)

Internet service, initial URL [10-11](#)

IP addresses

- Captive Portal application [2-15](#)
- directory [2-11, 8-3, 12-8](#)
- load balancing [E-1](#)
- location awareness [10-4](#)
- RADIUS server [2-10, 2-14, 12-4, 12-5](#)
- RDP [2-13, 12-7](#)
- RDP clients [2-15](#)
- SSG [2-9, 12-2, 12-3, F-3](#)
- troubleshooting RADIUS server [13-9](#)

IP attribute [5-9](#)

iPlanet

- Console [B-6](#)
- dn [2-12, 5-6, 6-3](#)
- installing [B-1, B-4](#)
- password [2-11](#)
- tree and context [B-4](#)
- uid [2-11, 2-12](#)

iss file [2-4](#)

J

J2EE containers [3-1, 4-1, 13-9](#)
 J2EE listeners, eliminating [11-5](#)
 Jasper JSP framework [2-20](#)

Java

- memory usage [13-9](#)
- memory use [5-5, 9-8](#)
- security [A-1](#)
- virtual memory [8-2, 9-8](#)

javadoc [2-20](#)

Java Management Extensions

See JMX

Java Secure Sockets Extension [A-2](#)

Java system properties

- See system properties

JAXP XML parser, installing [2-20](#)

JDK

- installing [1-5](#)
- locating [1-4, 13-6](#)
- messages at startup [13-7](#)
- preinstalled [13-7](#)
- SESM startup scripts [1-4](#)
- specifying location [1-4](#)

JDK_HOME [1-4, 1-5, 9-4](#)

jetty.home [4-5, 4-7, 9-5](#)

jetty.log [4-4, 13-4](#)

Jetty server

- certificates [A-2](#)
- configuring [4-2](#)
- installing [2-7](#)
- log files [13-4](#)
- port-bundle host key [4-1, 4-2](#)
- starting [9-1](#)
- stopping [9-6](#)
- troubleshooting [13-4, 13-9](#)
- See also J2EE containers

JIT relocation message [13-7](#)

JMX

- description [3-1](#)
- HTML Adaptor server [3-5](#)
- installing framework [2-20](#)
- path [2-20](#)
- server [3-1, 3-3, 5-19](#)

JRE

- installing [1-3](#)
- locating [1-4, 13-6](#)
- messages at startup [13-7](#)
- preinstalled [13-7](#)
- SESM startup scripts [1-4](#)
- specifications [1-3](#)

- specifying location 1-4
 - JSPs
 - description 5-19
 - framework path 2-20
 - installing framework 2-20
 - precompiling 2-20
 - recompiling 1-5
 - recompiling after changing 13-7
 - JSSE A-2
 - JVM
 - arguments 9-8
 - location 1-4, 9-4
 - RDP 9-9
 - jvm arguments
 - changing 13-9
-
- K**
- KeyPassword attribute 4-7
 - keys, next hop gateway C-8, C-16
 - keystore 4-7, A-2
 - Keystore attribute 4-7
 - keytool facility A-2
-
- L**
- LDAP directory
 - See directory
 - LDAP mode
 - communication attributes summary 12-6
 - setting 5-4
 - lib.xml 6-1
 - license
 - obtaining number 2-1, 2-6
 - types, for installation 2-6
 - licensenum.txt file 2-6, 2-20
 - links, on CDAT main window 2-19
 - links attribute 6-3
 - Linux
 - stopping applications 9-6
 - supported platforms 1-1
 - well-known locations for JRE 13-6
 - load balancing E-1
 - configuring with SSG E-1
 - port-bundle host key E-2
 - SESM IP address for E-1
 - stickiness E-2
 - loads, SSG tuning 5-8
 - LOCAL attribute 7-2
 - locale 10-4
 - LOCAL mode, RDP 7-2
 - localPort attribute 7-6, D-5
 - LOCATION attribute 10-5
 - location awareness
 - compared to locale 10-4
 - complete ID 10-4, 10-5, 10-8
 - configuring 5-15, 10-4
 - demonstrating 10-8
 - description 10-3
 - duplicates 10-6
 - images 10-5
 - IP subnets 10-4
 - location names 10-5
 - nested 10-6
 - overlapping 10-6
 - parameters 5-9
 - URLs 10-11
 - user shape 10-5
 - Location MBean 5-15, 10-4
 - locations attribute 5-15
 - locationService attribute 5-15
 - logDateFormat attribute 4-3, 5-3
 - logFile attribute 5-3
 - logFrame attribute 5-3
 - Logger MBean 5-2
 - logging off
 - portal applications 5-14

- with automatic connections 10-3
 - logging on
 - to AgentView 6-4
 - to CDAT 6-3, 6-5, 8-3
 - to portal applications 9-5
 - to services 11-8, 11-11, 11-17
 - with automatic connections 10-2
 - logLabels attribute 4-3
 - Log MBean 4-3
 - logOneLine attribute 4-3
 - logs
 - application.home 4-4, 9-5
 - application.log 5-3, 13-4
 - configuring 4-3, 5-2
 - directory activity 8-2
 - file names 13-4
 - filenames 4-4, 5-3
 - installation activity 2-5
 - jetty.home 9-5
 - jetty.log 4-4, 13-4
 - Jetty server activity 4-3
 - portal activity 5-2
 - RDP console 7-5
 - request.log 4-5, 13-4
 - turning off 5-2
 - logStack attribute 5-3
 - logStackSize attribute 4-3
 - logStackTrace attribute 4-3
 - logTags attribute 4-3
 - logThread attribute 5-3
 - logTimeStamps attribute 4-3
 - logTimezone attribute 4-3
 - logToErr attribute 5-3
-
- M
- MainServlet MBean 6-2
 - management.portno 9-5
 - management console
 - configuring 3-5
 - port 2-8, 3-5, 9-4
 - removing 3-5
 - starting 3-5
 - See also HTML Adaptor server
 - ManagementConsole MBean 3-5, 5-3
 - mapping SSGs to clients 5-7, 5-18
 - MASK attribute 5-7, 5-9
 - masks 2-9, 5-19
 - MaxIdleTimeMs attribute 4-7
 - maxIdleTimeMs attribute 4-6
 - maximum length, usernames and passwords 5-14
 - maximum transmission unit C-8
 - maxReadTimeMs attribute 4-6
 - MaxThreads attribute 4-7
 - maxThreads attribute 4-6, 7-6, D-5
 - maxVariables attribute 6-4
 - MBeans
 - AAA 5-10
 - captiveportal 11-11
 - CDAT 6-3, 7-3, 11-10, 11-13, D-2
 - changing 3-1
 - changing attribute values 3-2
 - comments in 3-11
 - ConfigAgent 3-17
 - Connection 8-3
 - constructing and initializing 3-17
 - Debug 4-2, 4-4
 - description 3-2, 3-17
 - DESSMode 5-6, 11-14
 - Directory 8-1, 8-2
 - Firewall 5-11
 - Jetty 4-2
 - Location 5-15, 10-4
 - Log 4-2, 4-3
 - Logger 5-2, 7-3, 11-10, 11-13, D-2
 - MainServlet 6-2
 - ManagementConsole 5-3, 7-3, 11-10, 11-13, D-2
 - messageportal 11-15

- property tags in [3-11](#)
- RADIUSDictionary [7-4](#)
- RDP [7-4](#)
- read-only attributes [3-2](#)
- read-write attributes [3-2](#)
- Server [4-5](#)
- SESM [5-4, 11-14](#)
- SESMDemoMode [5-6, 11-14](#)
- SESMSocketListener [4-6](#)
- SESMSSLListener [4-7](#)
- SSG [5-7, 10-4](#)
- WebApp [5-13, 11-16](#)
- MBean View [3-4, 3-9](#)
- memory
 - argument in startup script [9-8](#)
 - directory cache [8-2](#)
 - exceptions [9-8, 13-9](#)
 - portal applications [5-5, 9-8](#)
 - RDP [9-9](#)
 - requirements summary [1-2](#)
 - reserved [9-8](#)
 - setting java virtual memory [9-8](#)
 - SSG [5-5, 7-2](#)
 - use [5-5, 9-8](#)
- memRequired attribute [5-5](#)
- message duration
 - See duration
- messageportal.host [11-11](#)
- messageportal.jetty.xml [3-14](#)
- messageportal.port [11-11](#)
- messageportal.xml [3-14, 11-13, 11-15](#)
- Message Portal application
 - configuring [11-15](#)
 - description [11-4](#)
 - installing [2-15](#)
 - ports [2-16](#)
 - running in secure mode only [A-4](#)
 - timing of durations [11-4](#)
- messageportal MBean [11-15](#)
- messageRedirectDurationParam attribute [11-13](#)
- messageRedirectSubscriberParam attribute [11-13, 11-25](#)
- messageRedirectURLParam attribute [11-13](#)
- messages
 - at startup [13-7](#)
- meta schema, directory [2-12](#)
- Microsoft Windows
 - adding and removing services [9-7](#)
 - platform specifications [1-1](#)
 - stopping applications [9-7](#)
- minimum length, usernames and passwords [5-14](#)
- MinThreads attribute [4-7](#)
- minThreads attribute [4-6, 7-5, D-4](#)
- missing files [13-8](#)
- mode
 - argument to startup scripts [9-2](#)
 - attribute [5-4](#)
 - concurrent service [C-7](#)
 - configuration setting [5-4](#)
 - console installation [2-4](#)
 - GUI installation [2-3](#)
 - installation [2-3](#)
 - RDP [7-2](#)
 - running secure-only mode [A-3](#)
 - sequential service [C-7](#)
 - silent installation [2-4](#)
 - switching deployment [2-7, 5-4](#)
 - system property [5-4](#)
- modes
 - RDP [7-2](#)
 - secure [A-3](#)
- monitoring applications [3-2, 3-12](#)
- MSISDN [C-11](#)
- MTU, PPP [C-8](#)
- multikey authentication [7-5, 10-28](#)
- mutually exclusive service groups [5-5, C-10](#)
- My Firewall page [5-11, 10-14](#)

N

- naming attribute [2-12, 6-3](#)
- NAS [C-1, C-2, C-11](#)
- NDS
 - Allow Clear Text Passwords [B-3](#)
 - authenticating [B-3](#)
 - container cn [2-12](#)
 - directory cn [2-11](#)
 - directory dn [2-12, 5-6, 6-3](#)
 - directory password [2-11](#)
 - installing [B-1](#)
 - tree and context [B-1](#)
- nested locations [10-6](#)
- next hop
 - gateway [C-8, C-16](#)
 - password [2-13, 7-5, 12-4](#)
- nextHopPassword attribute [7-5](#)
- noSubscribePermissionURI attribute [5-14, 11-17](#)
- Novell eDirectory
 - See NDS
- NWSP
 - installing [2-7](#)
 - port [2-8](#)
 - role in captive portal solution [11-4](#)
 - starting [9-1](#)
 - virtual memory [8-2](#)
- nwsp.jetty.xml [3-14, 4-2](#)
- nwsp.xml [3-14, 5-2, 11-16](#)

O

- organization, LDAP directory [2-12, 12-8](#)
- original subscriber URL
 - See URLs
- outacls [10-16, 10-22](#)
- out of memory exception [13-9](#)
- out of memory exceptions [9-8](#)
- overlapping locations [10-6](#)

P

- PAP [C-7](#)
- parent account, Demo mode [C-14](#)
- passthrough services [C-7](#)
- passwordMaxLength attribute [5-14](#)
- passwordMinLength attribute [5-14](#)
- passwords
 - Allow Clear Text Passwords [B-3](#)
 - attributes for RDP [12-7](#)
 - directory [2-11, 8-3](#)
 - directory container [2-12](#)
 - keystore [4-7](#)
 - length [5-14](#)
 - next hop [2-13, 7-5](#)
 - service [2-10, 2-13, 5-10, 7-5, 12-4, 12-5, 13-9](#)
 - service group [2-10, 2-13, 7-5](#)
- path names, of configuration files [13-8](#)
- PDA
 - application port [2-8](#)
 - installing [2-7](#)
- pda.jetty.xml [3-14](#)
- pda.xml [3-14, 5-2](#)
- permissions
 - Demo mode [C-13](#)
 - LDAP directory [2-11, 2-12](#)
 - required for installation [2-3, 13-8](#)
- persisting attribute changes [3-11](#)
- personal firewalls [10-12](#)
- platforms, hardware [1-1](#)
- policies, mapping SSG to clients [5-7](#)
- poolSize attribute [8-3](#)
- PORT_BUNDLE_HOST_KEY_SWITCH attribute [5-8](#)
- portals
 - configuring [2-8, 5-1](#)
 - CPU utilization [9-7](#)
 - defined as NAS client [C-2](#)
 - directory communication [12-9](#)
 - J2EE containers [4-1](#)

- logging on 9-5
- memory requirements 9-7
- names 5-20, 9-3
- ports 2-8
- RADIUS communication 2-10, 12-5
- running in secure mode A-3
- SSG communication 2-9, 12-2
- starting 9-3
- stopping 9-6
- timeouts 5-8
- troubleshooting 13-1
- PORT attribute 5-7, 5-9, 12-2
- PortBundleHandler 4-2
- port-bundle host key
 - bundle length 5-8, 12-2, 12-3
 - Cisco IOS release F-2
 - configuring 4-2, F-2
 - description 4-1, 5-16
 - IP addresses F-3
 - Jetty 4-1
 - Jetty server 4-2
 - load balancing E-2
 - location awareness 10-4
 - port bundles 2-9, 5-18
- port-lists 11-19
- port-map F-3
- ports
 - accounting C-1
 - advertising redirection 2-17
 - application.portno 9-5
 - application.ssl.portno 9-5
 - authentication C-1
 - Captive Portal application 2-15
 - CDAT 2-19
 - directory 2-11, 8-3, 12-8
 - initial logon redirection 2-17
 - Jetty listener 4-6
 - management.portno 9-5
 - management console 2-8, 3-5, 9-4, 9-5
 - Message Portal application 2-16
 - portal applications 2-8, 9-3, 9-5
 - RADIUS server 2-10, 2-14, 5-10, 7-7, 12-4
 - RDP 2-13, 12-7
 - service redirection 2-18
 - SSG 2-9, 5-7, 5-9, 12-2, 13-8
 - SSL 2-8, 4-7, 9-4, 9-5, A-3
 - startup scripts 9-3
 - troubleshooting 13-9, 13-10
 - unauthenticated user redirection 2-16
- PPP
 - connections 11-20
 - maximum transmission unit C-8
 - single sign-on 5-4
 - subscriber profiles C-12
- precompiling JSPs 2-20
- predefined attributes C-3
- prepaidRedirectionURL attribute 5-14, 11-16
- primaryIP attribute 5-10, 7-7
- primaryPort attribute 5-10, 7-7
- principal attribute, SPE 8-3
- printTraceToConsole, DESS 8-2
- priorities, firewalls 10-13
- privileges
 - See permissions
- profileCachePeriod attribute 5-5
- profiles
 - ACLs C-9, C-15
 - caching 5-5
 - defining new attributes C-5
 - examples C-9, C-10, C-15, C-19
 - for Demo mode C-13
 - next hop gateway C-16
 - PPP subscribers C-12
 - service C-6
 - service group 5-10, C-10
 - subscriber C-11
- properties files 2-4
 - See also system properties; aaa.properties file

Property tag, in XML files [3-11, 3-17](#)

protocols

CHAP [C-7](#)

handlers, RDP [7-8](#)

on firewall pages [5-11, 10-17](#)

PAP [C-7](#)

proxy

RDP mode [2-14, 7-2, 12-9](#)

service type [C-7](#)

Proxy mode, RDP [7-2](#)

Q

quality of service [10-28, C-8, C-13](#)

queryMaxResults attribute [6-4](#)

query parameters, HTTP redirections [11-3](#)

queryTimeout attribute [6-4](#)

R

RADIUS

\$ subattributes [C-13](#)

AAA MBean [5-10](#)

access accept messages [C-13](#)

attributes [7-4](#)

clients [12-5, C-1](#)

dictionary [7-4, C-2](#)

mode [5-4, 12-3](#)

password [F-2](#)

predefined attributes [C-3](#)

primary server [2-10, 2-14](#)

requirements for SESM installation [1-5](#)

secondary server [2-10, 2-14, 12-5](#)

RADIUS Data Proxy

See RDP

RADIUSDictionary MBean [7-4](#)

RADIUS server

accounting port [C-1, C-16](#)

authentication port [C-1](#)

bundled SESM [D-1](#)

installing bundled [2-7](#)

portal communication [2-10, 2-14, 12-5, 13-9](#)

RDP communication [12-10](#)

SSG communication [12-4, 13-9](#)

troubleshooting [13-9](#)

See also ports

radius-server parameter [13-10](#)

RADIUS shared secret

configuring on RADIUS server [C-2](#)

with portals [2-10](#)

with RDP [2-14](#)

with SSG [2-9](#)

RAM [1-2, 9-8, 9-9](#)

RBAC [2-19, 8-3](#)

RDP

adding clients [2-14, 7-6](#)

Add Services option [2-14, 7-2](#)

authentication [7-8](#)

automatic connections [5-5, 7-2, 10-2](#)

caching [10-3](#)

client IP addresses [2-15](#)

console messages [7-5](#)

defining new attributes [7-4](#)

directory communication [12-8](#)

handlers [7-1, 7-5](#)

installing [2-7, 2-13](#)

IP address [2-13, 12-7](#)

listeners [7-1](#)

LOCAL mode [7-2](#)

memory requirements [9-9](#)

modes [7-2](#)

next hop password [2-13, 7-5](#)

port [2-13, 12-7](#)

protocol handlers [7-8](#)

RADIUS communication [2-14, 12-10](#)

restricted client feature [2-13, 2-14, 7-6, D-5](#)

service password [2-13, 12-7](#)

- shared secret [2-13, 2-14, 2-15](#)
 - SSG communication [2-13, 12-7](#)
 - starting [9-2](#)
 - stopping [9-6](#)
 - troubleshooting [13-3](#)
 - virtual memory [8-2](#)
 - See also Proxy mode; RDP
 - rdp.xml [3-14, 7-3](#)
 - RDP MBean [7-4](#)
 - README.SESM.LDIF.html file [2-20](#)
 - read-only attributes, in MBeans [3-2](#)
 - read-write attributes, in MBeans [3-2](#)
 - recompiling JSPs [1-5, 13-7](#)
 - redirectOn attribute [11-15](#)
 - refresh interval [3-2](#)
 - registering MBeans [3-17](#)
 - releases
 - See Cisco IOS
 - Reload button [3-10](#)
 - reload interval [3-10](#)
 - remote management tool [3-3](#)
 - See also Agent View
 - request.log [4-5, 13-4](#)
 - reserved memory [9-8](#)
 - restricted client feature
 - See RDP
 - retainDays attribute [4-4, 4-5](#)
 - RETRIES attribute [5-7](#)
 - retryCount attribute [5-10, 7-7](#)
 - returnOption attribute [5-13](#)
 - roles, loading [2-19](#)
-
- S
- sample LDAP data [8-4](#)
 - schema, extending [2-19, 8-3](#)
 - secondaryIP attribute [5-10, 7-7](#)
 - secondaryPort attribute [5-10, 7-7](#)
 - SECRET attribute [5-7, 5-9, 12-2](#)
 - secret attribute [5-10, 7-6, 7-7](#)
 - secure socket listener
 - See SSL
 - security [A-1](#)
 - self-subscription, Demo mode [C-13](#)
 - sequential service mode [C-7](#)
 - Server MBean [4-5](#)
 - servers
 - See Jetty Server; J2EE; JMX; RADIUS Server
 - service
 - connection [5-14](#)
 - cookies [C-8](#)
 - destinations [C-7](#)
 - groups
 - in service profiles [C-12](#)
 - mutually exclusive [5-5, C-10](#)
 - password [2-10, 2-13, 5-10, 7-5, 12-5](#)
 - profiles [C-10](#)
 - idle timeout [C-7](#)
 - logons [11-8, 11-11, 11-17](#)
 - names [2-18, C-12](#)
 - next hop gateway [C-8](#)
 - object, SSG [C-7](#)
 - passthrough [C-7](#)
 - password [7-5](#)
 - proxy [C-7](#)
 - query parameter in HTTP redirection [11-3](#)
 - routes [11-24](#)
 - status [10-2](#)
 - timeouts [C-7](#)
 - tunnel [C-7](#)
 - types [C-10](#)
 - URL [11-3](#)
 - See also automatic connections; profiles
 - service group name, Demo mode [C-13](#)
 - serviceGroup Password attribute [5-10](#)
 - serviceLogonURI attribute [5-14, 11-17](#)
 - serviceNotGivenURI attribute [2-18, 5-14, 11-4, 11-16](#)
 - servicePassword attribute [5-10, 7-5](#)

- serviceportal.host 11-11
- serviceportal.host system property 2-16
- serviceportal.port 2-16, 11-11
- service proxy C-7
- serviceRedirectDefaultURL attribute 11-9, 11-12
- service redirection
 - configuring 2-18, 11-11, 11-20
 - content application for 2-16
 - HTTP query parameters 11-3
 - login pages 11-8
 - ports 2-18
 - service names 2-18
 - service routes 11-24
 - shared address space 11-21
 - URL 11-12
- serviceRedirectOn attribute 11-11, 11-24
- serviceRedirectServiceParam attribute 11-13
- serviceRedirectSubscriberParam attribute 11-13, 11-25
- serviceRedirectURLParam attribute 11-13
- serviceStartURI attribute 5-14, 11-17
- serviceSubscriptionURI attribute 5-14, 11-17
- serviceURL query parameter 11-3
- sesm.mode 5-4
- SESMDemoMode MBean 5-6, 11-14
- SESM MBean 5-4, 11-14
- SESMSession object 10-5
- SESMSocketListener MBean 4-6
- SESMSSLListener MBean 4-7
- SESSION_BRAND 5-9
- SESSION_LOCATION 5-9
- sessionCachePeriod attribute 5-5
- sessionTimeout attribute 5-14
- sessionTimeout attribute 6-3
- session timeouts C-11
- setSubnetAttribute call 5-9
- setup type 2-7
- shared address spaces, service redirection 11-21
- shared secret
 - configuring on RADIUS C-2
 - description 12-3
 - RADIUS and portals 2-10, 5-10, 7-7, 12-5, 13-9
 - RADIUS and SSG 2-9, 5-7, 12-2, 12-4, F-2
 - RDP and RADIUS 2-14
 - RDP and SSG 2-13, 2-15, 12-7
 - SSG and portals 13-8
 - troubleshooting 13-10
- silent installation mode 2-4
- single sign-on 5-4, 10-3, C-14
- singleSignOn attribute 5-4
- SMTP redirection C-13
- Solaris
 - patches 1-3
 - platform specifications 1-1
 - stopping applications 9-6
 - well-known locations for JRE 13-6
- source ip command F-3
- space requirements 1-2
- SPE
 - caching 8-2
 - configuration file 8-1
 - installing 2-7
 - virtual memory 8-2
- specifications
 - disk space 1-2
 - Java 1-3
 - RAM 1-2, 9-8, 9-9
- SSG
 - clients to RDP 2-15
 - complete ID 10-4, 10-5, 10-8
 - configuring 2-9, 5-16, F-1
 - defining as NAS client C-2
 - duration parameters 11-18
 - edge session C-11
 - explicit IP address 5-9
 - global attributes 5-7, 5-16
 - IP address 2-9, 12-2, 12-3, F-3
 - load balancing E-1
 - mapping clients 5-16

- mapping policies [5-7](#)
- mapping subnets [2-9, 5-18](#)
- MBean [5-7, 10-4](#)
- memory [5-5, 7-2](#)
- port [12-2, 12-3](#)
- portal communication [2-9, 12-2](#)
- port-map [F-3](#)
- RADIUS server communication [12-4, 13-9](#)
- RADIUS server ports [2-9, C-1](#)
- RDP communication [2-13, 12-7](#)
- releases [10-4, 11-7, F-2](#)
- requirements during SESM installation [1-5](#)
- service object [C-7](#)
- shared secret [2-9, 2-13, F-1](#)
- subnet attributes [5-9, 5-16](#)
- tuning SESM loads [5-8](#)
- See also TCP redirections; port-bundle host key
- ssgconfig.txt [11-7, 11-8](#)
- SSGIPPolicyClass [5-7](#)
- SSL [2-8, 4-7, 9-4](#)
 - certificates [A-2](#)
 - port number [9-5](#)
 - running secure-only mode [A-3](#)
- stackTrace, DESS [8-2](#)
- starting
 - bundled RADIUS server [D-2](#)
 - CDAT [9-3](#)
 - error messages [13-7](#)
 - Jetty server [9-1](#)
 - portals [9-1](#)
 - RDP [9-2](#)
- startup scripts
 - application names in [5-20, 9-3](#)
 - application-specific [9-3](#)
 - captive portal [11-9](#)
 - customizing [5-20](#)
 - description [9-3](#)
 - failure [13-4](#)
 - generic [9-4](#)
 - HTTPS mode [A-3](#)
 - Java system properties [3-18, 9-4, 9-5](#)
 - JDK_HOME [1-4, 9-4](#)
 - JDK reference [1-4, 1-5](#)
 - JRE reference [1-4](#)
 - jvm arguments [9-8, 13-9](#)
 - memory [9-8, 9-9](#)
 - mode argument [9-2](#)
 - port references [9-3](#)
 - status, of services [10-2](#)
 - stickiness [E-2](#)
 - stopping SESM processes [9-6](#)
 - Store button [3-11](#)
 - subinterface, in location awareness [10-4](#)
 - subnet attributes, SSG [2-9, 5-9, 5-16](#)
 - subscriber name [11-3](#)
 - subscriber profiles
 - See profiles
 - Sun ONE
 - dn [2-12](#)
 - installing [B-1, B-4](#)
 - password [2-11](#)
 - tree and context [B-4](#)
 - uid [2-11, 2-12](#)
 - Sun Solaris
 - See Solaris
 - support, technical [2-6](#)
 - suppressStack attribute [4-4](#)
 - suppressWarnings attribute [4-4](#)
 - system properties [3-17, 9-4, 9-5](#)
 - SystemProperty tag, in XML files [3-11, 3-17](#)

T

 - tar files [2-2](#)
 - TCP redirections
 - configuring [11-7](#)
 - eliminating types [11-5](#)
 - SMTP forwarding [C-13](#)

types [11-3](#)

See also advertising redirection; initial logon redirection; service redirection; unauthenticated user redirection

technical support [2-6](#)

Telnet interface [F-3](#)

temporary disk space [1-2](#)

This [10-22](#)

THROTTLE attribute [5-8](#)

throttle attribute [5-10, 7-6](#)

timeOut attribute [5-10, 7-6](#)

timeouts

- CDAT [6-4](#)
- portals [5-8](#)
- service [C-7](#)
- service profile [C-7](#)
- session [C-11](#)

TIMEOUTSECS attribute [5-7](#)

tokenCheckInterval attribute [5-6](#)

tokenMaxAge attribute [5-6](#)

tools directory [2-20](#)

trace attribute [5-3](#)

traceFileName, DESS [8-2](#)

traceLevel, DESS [8-2](#)

tree, LDAP directory [12-8, B-1, B-4](#)

troubleshooting

- automatic connections [10-2](#)
- captive portal solution [11-23](#)
- CDAT [6-1](#)
- configuration file location [13-8](#)
- diagnostic procedures [13-1](#)
- JRE location [13-6](#)
- RDP [13-3](#)
- SESM portal applications [13-1, 13-8](#)
- web server [13-9](#)

tuning CDAT sessions [6-3](#)

tunnel services [C-7, C-9](#)

typical installation [2-7](#)

U

uid [2-12, 5-6, 6-3, B-4](#)

unauthenticated user redirection

- configuring [2-16, 11-11, 11-20](#)
- HTTP query parameters [11-3](#)
- port [2-16](#)

unavailable web server [13-9](#)

unconnected service redirection

- See service redirection

Undo button [3-11](#)

uninstalling SESM [1-6, 2-20](#)

unique identifier [2-12, 5-6, 6-3](#)

Unregister button [3-10](#)

URL

- initial [10-11](#)
- location-based [10-11](#)
- service redirection [11-12](#)
- unconnected service redirection [11-12](#)

URLs

- AgentView [3-6](#)
- attribute for LDAP server [8-3](#)
- destination, for service redirections [11-9](#)
- home page [C-12](#)
- service [C-8](#)
- subscriber's original
 - availability [11-6, 11-15](#)
 - Captive Portal application [11-3, 11-5](#)
 - duration before redirecting [11-17](#)
 - Message Portal [11-4, 11-12, 11-15](#)
 - parameter specifying [11-3, 11-13](#)

user

- groups, in Demo mode [C-13](#)
- ID, for directory [2-11, 8-3, 12-8](#)
- ID, for directory container [2-12, 8-2](#)
- shape [10-4, 10-5](#)

username

- full name in service profiles [C-8](#)
- length [5-14](#)

query parameter in HTTP redirection [11-3](#)
 usernameMaxLength attribute [5-14](#)
 usernameMinLength attribute [5-14](#)
 userRedirectOn attribute [11-11, 11-24](#)
 userRedirectPort attribute [11-12](#)
 userRedirectURL attribute [11-11](#)
 userRedirectURLParam attribute [11-13](#)

V

vendor-specific attributes

See VSAs

verbose attribute [4-4](#)

virtual

host name [4-5](#)

memory [8-2, 9-8, 9-9](#)

private dial-up network (VPDN) [C-9](#)

VPI, location awareness parameter [10-4](#)

VSAs [C-2, C-3](#)

W

WAP

application port [2-8](#)

installing [2-7](#)

wap.jetty.xml [3-14](#)

wap.xml [3-14, 5-2](#)

WAR files [4-2](#)

warning

during installation [2-11](#)

in log files [5-2](#)

logging configuration attribute [5-3](#)

web.xml [2-20, 3-18, 13-8](#)

webapp directory [2-20](#)

WebApp MBean [5-13, 11-16](#)

web archive files

See WAR files

webdefault.xml [3-18](#)

WEB-INF directory [2-20](#)

web-jetty.xml file [2-20, 3-19, 4-2](#)

web portals

See portals

Web Services Gateway [2-7](#)

Windows

See Microsoft Windows

WSG [2-7](#)

X

xmlconfig.dtd [3-15](#)

XML files

See J2EE configuration files; files

X server [13-7](#)

Z

zip files [2-2](#)

